

Safety Data Sheet

According to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 Revision date: 21/08/2020 Date of issue: 01/05/2014

Version: 4.0

SECTION 1: Identification of the Substance/mixture and of the Company/Undertaking

Product Identifier 1.1.

Product form Mixture Product Name CF1-141

Synonyms Silicone Primer

Relevant Identified Uses of the Substance or Mixture and Uses Advised Against 1.2.

1.2.1. Relevant Identified Uses

Use of the Substance/Mixture For professional use only.

1.2.2. Uses Advised Against

No additional information available

Details of the Supplier of the Safety Data Sheet

NuSil Technology Europe 1198 Avenue Maurice Donat Le Natura Bt. 2 06250 Mouains France +33 4 92 96 93 31

ehs@nusil.com www.nusil.com

Emergency Telephone Number

Emergency Number : 800-424-9300 CHEMTREC (in US); +1 703-527-3887 CHEMTREC

(International and Maritime)

+(44)-870-8200418 +(353)-19014670

SECTION 2: Hazards Identification

Classification of the Substance or Mixture

Classification According to Regulation (EC) No. 1272/2008 [CLP]

Flam. Lia. 2 H225 Eye Dam. 1 H318 STOT SE 3 H336

Full text of hazard classes and H-statements: see section 16

Label Elements

Labelling According to Regulation (EC) No. 1272/2008 [CLP]

Hazard Pictograms (CLP)





GHS02

Danger

Signal Word (CLP)

Hazardous Ingredients Isopropyl alcohol; 1-Butanol, titanium(4+) salt; Platinum Catalyst

H225 - Highly flammable liquid and vapour. Hazard Statements (CLP)

H318 - Causes serious eye damage. H336 - May cause drowsiness or dizziness.

21/08/2020 EN (English) 1/14

Precautionary Statements (CLP)

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233 - Keep container tightly closed.

P240 - Ground and bond container and receiving equipment.

P241 - Use explosion-proof electrical, ventilating, and lighting equipment.

P242 - Use non-sparking tools.

P243 - Take action to prevent static discharges.

P261 - Avoid breathing vapours, mist, or spray.

P271 - Use only outdoors or in a well-ventilated area.

P280 - Wear protective gloves, protective clothing, and eye protection.

P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.

P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 - Immediately call a POISON CENTER or doctor.

P312 - Call a POISON CENTRE or doctor if you feel unwell.

P370+P378 - In case of fire: Use appropriate media (see section 5) to extinguish.

P403+P233 - Store in a well-ventilated place. Keep container tightly closed.

P403+P235 - Store in a well-ventilated place. Keep cool.

P405 - Store locked up.

P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other Hazards

Other Hazards Not Contributing to the Classification

Exposure may aggravate pre-existing eye, skin, or respiratory conditions.

SECTION 3: Composition/Information on Ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product Identifier	%	Classification According to Regulation (EC) No. 1272/2008 [CLP]
Isopropyl alcohol	(CAS-No.) 67-63-0 (EC-No.) 200-661-7 (EC Index-No.) 603-117-00-0	70 - 90	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
1-Butanol, titanium(4+) salt	(CAS-No.) 5593-70-4 (EC-No.) 227-006-8	< 5	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H336 STOT SE 3, H335

21/08/2020 EN (English) 2/14

Safety Data Sheet

According to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Name	Product Identifier	%	Classification According to Regulation (EC) No. 1272/2008 [CLP]
Platinum Catalyst	(CAS-No.) 68478-92-2	< 5	Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H335
1-Butanol	(CAS-No.) 71-36-3 (EC-No.) 200-751-6 (EC Index-No.) 603-004-00-6	<1	Flam. Liq. 3, H226 Acute Tox. 4 (Oral), H302 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H335 STOT SE 3, H336

Full text of H-statements: see section 16

SECTION 4: First Aid Measures

4.1. Description of First-aid Measures

450105
Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
When symptoms occur: go into open air and ventilate
suspected area. Obtain medical attention if breathing difficulty
persists.
Immediately remove contaminated clothing. Immediately
drench affected area with water for at least 15 minutes. Obtain medical attention if irritation develops or persists.
Immediately rinse with water for at least 30 minutes. Remove
contact lenses, if present and easy to do. Continue rinsing. Get immediate medical advice/attention.
Rinse mouth. Do NOT induce vomiting. Obtain medical

4.2. Most Important Symptoms and Effects Both Acute and Delayed

attention.

T.E. Most important cympion	mis and Enecis Bom Acore and Belayea
Symptoms/Effects	Causes serious eye damage. May cause drowsiness and dizziness. Causes mild skin irritation.
Symptoms/Effects After Inhalation	High concentrations may cause central nervous system depression such as dizziness, vomiting, numbness, drowsiness, headache, and similar narcotic symptoms.
Symptoms/Effects After Skin	Causes mild skin irritation.

Contact

Ingestion

Symptoms/Effects After Eye

Contact

Symptoms/Effects After

Ingestion

Causes permanent damage to the cornea, iris, or conjunctiva.

Ingestion may cause adverse effects.

Chronic Symptoms Repeated or prolonged skin contact may cause irritation.

4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed If exposed or concerned, get medical advice and attention. If medical advice is needed, have product container or label at hand.

21/08/2020 EN (English) 3/14

SECTION 5: Firefighting Measures

5.1. Extinguishing Media

Suitable Extinguishing Media Water spray, fog, alcohol-resistant foam, carbon dioxide (CO₂),

dry chemical powder.

Unsuitable Extinguishing Media Do not use a heavy water stream. A heavy water stream may

spread burning liquid.

5.2. Special Hazards Arising From the Substance or Mixture

Fire Hazard Highly flammable liquid and vapour. Vapours are heavier than

air and may travel considerable distance to an ignition source

and flash back to source of vapours.

Explosion Hazard May form flammable or explosive vapour-air mixture. Heating

will cause rise in pressure with risk of bursting.

Reactivity Reacts violently with strong oxidisers. Increased risk of fire or

explosion. Hydrolysis in water.

5.3. Advice for Firefighters

Precautionary Measures Fire Exercise caution when fighting any chemical fire.

Firefighting Instructions

Use water spray or fog for cooling exposed containers. In case

of major fire and large quantities: Evacuate area. Fight fire

remotely due to the risk of explosion.

Protection During Firefighting Do not enter fire area without proper protective equipment,

including respiratory protection.

SECTION 6: Accidental Release Measures

6.1. Personal Precautions, Protective Equipment and Emergency Procedures

General Measures Do not breathe vapour, mist or spray. Do not get in eyes, on

skin, or on clothing. Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking. Use

special care to avoid static electric charges.

6.1.1. For Non-Emergency Personnel

Protective Equipment Use appropriate personal protective equipment (PPE).

Emergency Procedures Evacuate unnecessary personnel. Stop leak if safe to do so.

6.1.2. For Emergency Responders

Protective Equipment Equip cleanup crew with proper protection.

Emergency Procedures Upon arrival at the scene, a first responder is expected to

recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit. Ventilate area.

Eliminate ignition sources.

6.2. Environmental Precautions

Prevent entry to sewers and public waters.

6.3. Methods and Materials for Containment and Cleaning Up

For Containment Contain any spills with dikes or absorbents to prevent migration

and entry into sewers or streams. As an immediate

precautionary measure, isolate spill or leak area in all directions.

21/08/2020 EN (English) 4/14

According to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Methods For Cleaning Up Clean up spills immediately and dispose of waste safely.

Transfer spilled material to a suitable container for disposal. Do not take up in combustible material such as: saw dust or cellulosic material. Absorb and/or contain spill with inert material. Use only non-sparking tools. Contact competent

authorities after a spill.

6.4. Reference to Other Sections

See Section 8 for exposure controls and personal protection and Section 13 for disposal considerations.

SECTION 7: Handling And Storage

7.1. Precautions for Safe Handling

Additional Hazards When Handle empty containers with care because residual vapours

Processed are flammable.

Precautions for Safe Handling Avoid breathing vapours, mist, spray. Take precautionary

measures against static discharge. Use only non-sparking tools. Do not get in eyes, on skin, or on clothing. Wash hands and other exposed areas with mild soap and water before eating,

drinking or smoking and when leaving work.

Hygiene Measures Handle in accordance with good industrial hygiene and safety

procedures.

7.2. Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures Comply with applicable regulations. Take action to prevent

static discharges. Ground and bond container and receiving equipment. Use explosion-proof electrical, ventilating, and

lighting equipment.

Storage Conditions Store in a dry, cool place. Keep/Store away from direct sunlight,

extremely high or low temperatures and incompatible materials. Store locked up/in a secure area. Store in a well-ventilated place. Keep container tightly closed. Keep in

fireproof place.

Incompatible Materials Strong oxidizers. Strong acids. Acid anhydrides. Alkali metals.

Alkaline earth metals. Attacks some forms of plastics, rubber,

and coatings.

7.3. Specific End Use(S)

For professional use only.

SECTION 8: Exposure Controls/Personal Protection

8.1. Control Parameters

Isopropyl alcohol (67-6	53-0)	
Austria	MAK (mg/m³)	500 mg/m³
Austria	MAK (ppm)	200 ppm
Austria	MAK Short time value (mg/m³)	2000 mg/m³ 2000 mg/m³ (STEL for large casting valid until December 31, 2013)
Austria	MAK Short time value (ppm)	800 ppm 800 ppm (STEL for large casting valid until December 31, 2013)

21/08/2020 EN (English) 5/14

Safety Data Sheet According to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Austria	(REACH) with its amendment Regulation (EU) 2015/830 OEL chemical category (AT)	Group C Carcinogen by
		manufacturing of strong Acid process
Belgium	Limit value (mg/m³)	500 mg/m ³
Belgium	Limit value (ppm)	200 ppm
Belgium	Short time value (mg/m³)	1000 mg/m³
Belgium	Short time value (ppm)	400 ppm
Bulgaria	OEL TWA (mg/m³)	980 mg/m³
Bulgaria	OEL STEL (mg/m³)	1225 mg/m³
Croatia	GVI (granična vrijednost izloženosti) (mg/m³)	999 mg/m³
Croatia	GVI (granična vrijednost izloženosti) (ppm)	400 ppm
Croatia	KGVI (kratkotrajna granična vrijednost izloženosti) (mg/m³)	1250 mg/m³
Croatia	KGVI (kratkotrajna granična vrijednost izloženosti) (ppm)	500 ppm
Croatia	Croatia - BLV	50 mg/l Parameter: Acetone - Medium: blood - Sampling time: at the end of the work shift 50 mg/l Parameter: Acetone - Medium: urine - Sampling time: at the end of the work shift
Czech Republic	Expoziční limity (PEL) (mg/m³)	500 mg/m ³
Czech Republic	OEL chemical category (CZ)	Potential for cutaneous absorption
Denmark	Grænseværdie (langvarig) (mg/m³)	490 mg/m³
Denmark	Grænseværdie (langvarig) (ppm)	200 ppm
Estonia	OEL TWA (mg/m³)	350 mg/m³
Estonia	OEL TWA (ppm)	150 ppm
Estonia	OEL STEL (mg/m³)	600 mg/m³
Estonia	OEL STEL (ppm)	250 ppm
Finland	HTP-arvo (8h) (mg/m³)	500 mg/m³ (Propanol)
Finland	HTP-arvo (8h) (ppm)	200 ppm (Propanol)
Finland	HTP-arvo (15 min)	620 mg/m³
Finland	HTP-arvo (15 min) (ppm)	250 ppm
France	VLE (mg/m³)	980 mg/m³
France	VLE (ppm)	400 ppm
Germany	Occupational exposure limit value (mg/m³)	500 mg/m³ (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)
Germany	Occupational exposure limit value (ppm)	200 ppm (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)

EN (English) 21/08/2020 6/14

Safety Data Sheet According to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Germany	TRGS 903 Biological limit value	25 mg/l Parameter: Acetone - Medium: whole blood - Sampling time: end of shift 25 mg/l Parameter: Acetone - Medium: urine - Sampling time: end of shift
Greece	OEL TWA (mg/m³)	980 mg/m³
Greece	OEL TWA (ppm)	400 ppm
Greece	OEL STEL (mg/m³)	1225 mg/m³
Greece	OEL STEL (ppm)	500 ppm
Hungary	AK-érték	500 mg/m ³
Hungary	CK-érték	2000 mg/m ³
Hungary	OEL chemical category (HU)	Potential for cutaneous absorption
Ireland	OEL (8 hours ref) (ppm)	200 ppm
Ireland	OEL (15 min ref) (ppm)	400 ppm
Ireland	OEL chemical category (IE)	Potential for cutaneous absorption
Latvia	OEL TWA (mg/m³)	350 mg/m³
Lithuania	IPRV (mg/m³)	350 mg/m³
Lithuania	IPRV (ppm)	150 ppm
Lithuania	TPRV (mg/m³)	600 mg/m³
Lithuania	TPRV (ppm)	250 ppm
Norway	Grenseverdier (AN) (mg/m³)	245 mg/m³
Norway	Grenseverdier (AN) (ppm)	100 ppm
Norway	Grenseverdier (Korttidsverdi) (mg/m3)	306,25 mg/m³ (value calculated)
Norway	Grenseverdier (Korttidsverdi) (ppm)	125 ppm (value calculated)
Poland	NDS (mg/m³)	900 mg/m³
Poland	NDSCh (mg/m³)	1200 mg/m³
Portugal	OEL TWA (ppm)	200 ppm
Portugal	OEL STEL (ppm)	400 ppm
Portugal	OEL chemical category (PT)	A4 - Not Classifiable as a Human Carcinogen
Romania	OEL TWA (mg/m³)	200 mg/m³
Romania	OEL TWA (ppm)	81 ppm
Romania	OEL STEL (mg/m³)	500 mg/m ³
Romania	OEL STEL (ppm)	203 ppm
Romania	Romania - BLV	50 mg/l Parameter: Acetone - Medium: urine - Sampling time: end of shift
Slovakia	NPHV (priemerná) (mg/m³)	500 mg/m³
Slovakia	NPHV (priemerná) (ppm)	200 ppm
Slovakia	NPHV (Hraničná) (mg/m³)	1000 mg/m ³
Slovenia	OEL TWA (mg/m³)	500 mg/m³
Slovenia	OEL TWA (ppm)	200 ppm
Slovenia	OEL STEL (mg/m³)	1000 mg/m³

21/08/2020 7/14 EN (English)

Safety Data Sheet

According to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Slovenia	OEL STEL (ppm)	400 ppm
Spain	VLA-ED (mg/m³)	500 mg/m³ (the partial or complete commercialization or use of this substance as a phytosanitary or biocide compound is prohibited)
Spain	VLA-ED (ppm)	200 ppm (the partial or complete commercialization or use of this substance as a phytosanitary or biocide compound is prohibited)
Spain	VLA-EC (mg/m³)	1000 mg/m³
Spain	VLA-EC (ppm)	400 ppm
Spain	Spain - BLV	40 mg/l Parameter: Acetone - Medium: urine - Sampling time: end of workweek
Sweden	nivågränsvärde (NVG) (mg/m³)	350 mg/m³
Sweden	nivågränsvärde (NVG) (ppm)	150 ppm
Sweden	kortidsvärde (KTV) (mg/m³)	600 mg/m³
Sweden	kortidsvärde (KTV) (ppm)	250 ppm
Switzerland	KZGW (mg/m³)	1000 mg/m³
Switzerland	KZGW (ppm)	400 ppm
Switzerland	MAK (mg/m³)	500 mg/m³
Switzerland	MAK (ppm)	200 ppm
Switzerland	Switzerland - BLV	25 mg/l Parameter: Acetone - Medium: urine - Sampling time: end of shift 25 mg/l Parameter: Acetone - Medium: whole blood - Sampling time: end of shift
United Kingdom	WEL TWA (mg/m³)	999 mg/m³
United Kingdom	WEL TWA (ppm)	400 ppm
United Kingdom	WEL STEL (mg/m³)	1250 mg/m³
United Kingdom	WEL STEL (ppm)	500 ppm

8.2. Exposure Controls

Appropriate Engineering Controls

Ensure adequate ventilation, especially in confined areas. Ensure all national/local regulations are observed. Gas detectors should be used when flammable gases or vapours may be released. Proper grounding procedures to avoid static electricity should be followed. Use explosion-proof equipment. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Gloves. Protective clothing. Protective goggles. Insufficient ventilation: wear respiratory protection.

Personal Protective Equipment









Materials for Protective Clothing

Chemically resistant materials and fabrics. Wear fire/flame resistant/retardant clothing.

21/08/2020 EN (English) 8/14

Safety Data Sheet

According to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Hand Protection Wear protective gloves. Eye Protection Chemical safety goggles.

Skin and Body Protection Wear suitable protective clothing.

Respiratory Protection If exposure limits are exceeded or irritation is experienced,

approved respiratory protection should be worn. In case of inadequate ventilation, oxygen deficient atmosphere, or where

exposure levels are not known wear approved respiratory

protection.

Other Information When using, do not eat, drink or smoke.

SECTION 9: Physical and Chemical Hazards

9.1. Information on Basic Physical and Chemical Properties

Physical State Liquid
Colour Red
Odour Alcohol

Odour Threshold

pH

No data available

Flash Point 82 °C (180 °F) 12 °C (53 °F)

No data available **Auto-Ignition Temperature** Decomposition Temperature No data available Flammability (Solid, Gas) Not applicable Vapour Pressure No data available Relative Vapour Density At 20 °C No data available Relative Density < 1 (water = 1)Solubility No data available Partition Coefficient n-Octanol/Water No data available Viscosity, Kinematic No data available Viscosity, Dynamic No data available **Explosive Properties** No data available Oxidising Properties No data available **Explosive Limits** Not applicable

9.2. Other Information

VOC content 70 - 90 %

SECTION 10: Stability and Reactivity

10.1. Reactivity

Reacts violently with strong oxidisers. Increased risk of fire or explosion. Hydrolysis in water.

10.2. Chemical Stability

Extremely flammable liquid and vapour. May form flammable or explosive vapour-air mixture.

10.3. Possibility Of Hazardous Reactions

Hazardous polymerization will not occur.

21/08/2020 EN (English) 9/14

According to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

10.4. Conditions To Avoid

Direct sunlight, extremely high or low temperatures, heat, hot surfaces, sparks, open flames, incompatible materials, and other ignition sources.

10.5. Incompatible Materials

Strong oxidizers. Strong acids. Acid anhydrides. Alkali metals. Alkaline earth metals. Attacks some forms of plastics, rubber, and coatings.

10.6. Hazardous Decomposition Products

Thermal decomposition may produce: Hydrocarbons. Carbon oxides (CO, CO₂).

SECTION 11: Toxicological Information

11.1. Information On Toxicological Effects

Acute Toxicity

Not classified (Based on available data, the classification criteria are not met)

Isopropyl alcohol (67-63-0)	
LD50 Oral	4384 mg/kg
LD50 Dermal Rabbit	12956 mg/kg (16.4 mL/kg bw)
LC50 Inhalation Rat	72600 mg/m³ (Exposure time: 4 h)
1-Butanol, titanium(4+) salt (5593	-70-4)
LD50 Oral Rat	> 2000 mg/kg
LD50 Oral	3122 mg/kg

Skin Corrosion/Irritation Not classified (Based on available data, the classification

criteria are not met)

Eye Damage/Irritation Causes serious eye damage.

Respiratory or Skin Sensitization Not classified (Based on available data, the classification

criteria are not met)

Germ Cell Mutagenicity Not classified (Based on available data, the classification

criteria are not met)

Carcinogenicity Not classified (Based on available data, the classification

criteria are not met)

Reproductive Toxicity Not classified (Based on available data, the classification

criteria are not met)

Specific Target Organ Toxicity

(Single Exposure)

May cause drowsiness or dizziness.

Specific Target Organ Toxicity (Repeated Not classified (Based on available data, the

Exposure) classification criteria are not met)

Aspiration Hazard Not classified (Based on available data, the classification

criteria are not met)

SECTION 12: Ecological Information

12.1. Toxicity

Ecology - General Not classified.

Isopropyl alcohol (67-63-0)	
LC50 Fish 1	9640 mg/l (Exposure time: 96 h - Species: Pimephales
	promelas [flow-through])
EC50 Daphnia 1	13299 mg/l (Exposure time: 48 h - Species: Daphnia magna)

21/08/2020 EN (English) 10/14

Safety Data Sheet

According to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Isopropyl alcohol (67-63-0)	
EC50 Other Aquatic Organisms 1	1000 mg/l (Exposure time: 96 h - Species: Desmodesmus subspicatus)
LC50 Fish 2	11130 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 Other Aquatic Organisms 2	1000 mg/l (Exposure time: 72 h - Species: Desmodesmus subspicatus)
1-Butanol, titanium(4+) salt (5593-70)-4)
EC50 Daphnia 1	580 mg/l

12.2. Persistence and Degradability

CF1-141	•
Persistence and Degradability	Not established.

12.3. Bioaccumulative Potential

CF1-141		
Bioaccumulative potential Not established.		
Isopropyl alcohol (67-63-0)		
Log Pow	0,05 (at 25 °C)	

12.4. Mobility in Soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other Adverse Effects

Other Information Avoid release to the environment.

SECTION 13: Disposal Considerations

13.1. Waste Treatment Methods

Product/Packaging Disposal Dispose of contents/container in accordance with local,

Recommendations regional, national, and international regulations.

Additional Information Handle empty containers with care because residual vapours

are flammable.

SECTION 14: Transport Information

The shipping description(s) stated herein were prepared in accordance with certain assumptions at the time the SDS was authored, and can vary based on a number of variables that may or may not have been known at the time the SDS was issued.

In accordance with ADR / RID / IMDG / IATA / ADN

in decendance with but have a market have				
ADR	IMDG	IATA	ADN	RID
14.1. UN Number				
1219	1219	1219	1219	1219
14.2. UN Proper Shipping Name				
ISOPROPANOL	ISOPROPANOL	ISOPROPANOL	ISOPROPANOL	ISOPROPANOL
(ISOPROPYL	(ISOPROPYL	SOLUTION	(ISOPROPYL	(ISOPROPYL
ALCOHOL)	ALCOHOL)		ALCOHOL)	ALCOHOL)
SOLUTION	SOLUTION		SOLUTION	SOLUTION

21/08/2020 EN (English) 11/14

According to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

ADR	IMDG	IATA	ADN	RID
14.3. Transport Hazard Class(Es)				
3	3	3	3	3
3	3	3	3	3
14.4. Packing Group				
II			II	II
14.5. Environme	14.5. Environmental Hazards			
Dangerous for the environment : No	Dangerous for the environment : No Marine pollutant : No	Dangerous for the environment : No	Dangerous for the environment : No	Dangerous for the environment : No

14.6. Special Precautions For User

No additional information available

14.7. Transport in Bulk According to Annex II of MARPOL and The IBC Code

Not applicable

SECTION 15: Regulatory Information

15.1. Safety, Health and Environmental Regulations/Legislation Specific for the Substance or Mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions Contains no substance on the REACH candidate list Contains no REACH Annex XIV substances

15.1.2. National Regulations

No additional information available

15.2. Chemical Safety Assessment

No chemical safety assessment has been carried out

SECTION 16: Other Information

Indication of Changes

Section	Section Header	Change	Date Changed
1	Identification of the Substance/mixture and of the Company/Undertaking	Modified	21/08/2020
2	Hazards Identification	Modified	21/08/2020
3	Composition/Information on Ingredients	Modified	21/08/2020

Date of Preparation or Latest

21/08/2020

Revision

Data Sources

Information and data obtained and used in the authoring of this safety data sheet could come from database subscriptions,

official government regulatory body websites,

product/ingredient manufacturer or supplier specific

information, and/or resources that include substance specific data and classifications according to GHS or their subsequent

adoption of GHS.

21/08/2020 EN (English) 12/14

Other Information

According to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Full Text of H- and EUH-statements:

Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3,
	Respiratory tract irritation
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.

Abbreviations and Acronyms

ACGIH – American Conference of Governmental Industrial Hyaienists

ADN – European Agreement Concerning the International Carriage of Dangerous Goods by Inland Waterways

ADR - European Agreement Concerning the International Carriage of Dangerous

Goods by Road

ATE - Acute Toxicity Estimate BCF - Bioconcentration Factor BEI - Biological Exposure Indices (BEI)

BOD – Biochemical Oxygen Demand CAS No. - Chemical Abstracts Service Number

CLP – Classification, Labeling and Packaging Regulation (EC) No 1272/2008 COD – Chemical Oxygen Demand

EC - European Community EC50 - Median Effective Concentration

EEC - European Economic Community

EINECS - European Inventory of Existing Commercial Chemical Substances

EmS-No. (Fire) - IMDG Emergency Schedule Fire EmS-No. (Spillage) - IMDG Emergency Schedule Spillage

EU – European Union ErC50 - EC50 in Terms of Reduction Growth Rate

GHS – Globally Harmonized System of Classification and Labeling of Chemicals

IARC - International Agency for Research on Cancer IATA - International Air Transport Association

IBC Code - International Bulk Chemical Code IMDG - International Maritime Dangerous Goods

IPRV - Ilgalaikio Poveikio Ribinis Dydis

IOELV - Indicative Occupational Exposure Limit Value

LC50 - Median Lethal Concentration

LD50 - Median Lethal Dose

LOAEL - Lowest Observed Adverse Effect Level LOEC - Lowest-Observed-Effect Concentration

Log Koc - Soil Organic Carbon-water Partitioning Coefficient

Log Kow - Octanol/water Partition Coefficient

Log Pow - Ratio of the equilibrium concentration (C) of a dissolved substance in a two-phase system consisting of two largely immiscible solvents, in this case octanol and water

- Maximum Workplace Concentration/Maximum Permissible Concentration

MARPOL - International Convention for the Prevention of Pollution

NDS - Naiwyzsze Dopuszczalne Stezenie

NDSCh - Najwyzsze Dopuszczalne Stezenie Chwilowe NDSP - Najwyzsze Dopuszczalne Stezenie Pulapowe

NOAEL - No-Observed Adverse Effect Level

NOEC - No-Observed Effect Concentration NRD - Nevirsytinas Ribinis Dydis

NTP - National Toxicology Program

OEL - Occupational Exposure Limits

PBT - Persistent, Bioaccumulative and Toxic PEL - Permissible Exposure Limit

pH – Potential Hydrogen

REACH – Reaistration, Evaluation, Authorisation, and Restriction of Chemicals

RID – Regulations Concerning the International Carriage of Dangerous Goods by Rail

SADT - Self Accelerating Decomposition Temperature

SDS - Safety Data Sheet

STEL - Short Term Exposure Limit

STOT - Specific Target Organ Toxicity
TA-Luft - Technische Anleitung zur Reinhaltung der Luft

TEL TRK - Technical Guidance Concentrations

ThOD – Theoretical Oxygen Demand

TLM - Median Tolerance Limit TLV - Threshold Limit Value

TPRD - Trumpalaikio Poveikio Ribinis Dydis

TRGS 510 - Technische Regel für Gefahrstoffe 510 - Lagerung von Gefahrstoffen in

ortsbeweglichen Behältern

TRGS 552 – Technische Regeln für Gefahrstoffe - N-Nitrosamine

TRGS 900 - Technische Regel für Gefahrstoffe 900 – Arbeitsplatzgrenzwerte TRGS 903 - Technische Regel für Gefahrstoffe 903 - Biologische Grenzwerte

TSCA - Toxic Substances Control Act

TWA - Time Weighted Average VOC – Volatile Organic Compounds

VLA-EC - Valor Límite Ambiental Exposición de Corta Duración VLA-ED - Valor Límite Ambiental Exposición Diaria

VLE – Valeur Limite D'exposition

VME – Valeur Limite De Moyenne Exposition vPvB - Very Persistent and Very Bioaccumulative

 Workplace Exposure Limit WGK - Wassergefährdungsklasse

Nusil EU GHS SDS

The information provided in this Safety Data Sheet (SDS) was prepared based on data believed to be accurate as of the date of this SDS. TO THE GREATEST EXTENT PERMITTED BY LAW, NUSIL TECHNOLOGY LLC AND ITS AFFILIATED COMPANIES ("NUSIL") EXPRESSLYDISCLAIMS ANY AND ALL REPRESENTATIONS AND WARRANTIES REGARDING THE INFORMATION CONTAINED HEREIN INCLUDING, WITHOUT LIMITATION, AS TO ACCURACY, COMPLETENESS, FITNESS FOR PURPOSE OR USE, MERCHANTABILITY, NON-INFRINGEMENT, PERFORMANCE, SAFETY, SUITABILITY AND STABILITY. This SDS is intended as a guide to the appropriate use, handling, storage and disposal of

13/14

Safety Data Sheet

According to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

the product to which it relates by properly trained personnel, and is not intended to be comprehensive. Users of NuSil's products are advised to perform their own tests and to exercise their own judgment to determine the safety, suitability and appropriate use, handling, storage and disposal of each product and product combination for their own purposes and uses. TO THE GREATEST EXTENT PERMITTED BY LAW, NUSIL DISCLAIMS LIABILITY FOR, AND BY USING NUSIL'S PRODUCTS PURCHASER AGREES THAT UNDER NO CIRCUMSTANCES SHALL NUSIL BE LIABLE FOR, SPECIAL, INDIRECT, INCIDENTAL, PUNITIVE OR CONSEQUENTIAL DAMAGES OF ANY TYPE OR KIND, INCLUDING WITHOUT LIMITATION, FOR LOSS OF PROFITS, REPUTATIONAL DAMAGE, PRODUCT RECALL OR BUSINESS INTERRUPTION.

21/08/2020 EN (English) 14/14