### Hazard Pictograms (CLP) GHS02 GHS07 Signal Word (CLP) Danger Ethyl acetate Hazardous Ingredients Hazard Statements (CLP) H225 - Highly flammable liquid and vapour. H319 - Causes serious eye irritation. H336 - May cause drowsiness or dizziness. Precautionary Statements (CLP) P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. EN (English)

Label Elements

### Eye Irrit. 2 H319

STOT SE 3 H336

**Emergency Telephone Number** 

2.2.

Flam. Lig. 2 H225

**MED-1356** 

1.1.

1.2.

1.3.

France

1.4.

2.1.

Product form

Product Name Synonyms

Le Natura Bt. 2 06250 Mougins

+33 4 92 96 93 31 ehs@nusil.com www.nusil.com

**Emergency Number** 

Safety Data Sheet

Company/Undertaking

**Product Identifier** 

1.2.1. Relevant Identified Uses Use of the Substance/Mixture

No additional information available

1.2.2. Uses Advised Against

NuSil Technology Europe 1198 Avenue Maurice Donat

According to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 Revision date: 29/06/2021 Date of issue: 21/10/2014 Version: 3.0

SECTION 1: Identification of the Substance/mixture and of the

Mixture MED-1356

Details of the Supplier of the Safety Data Sheet

CHEMTREC (in US) +(44)-870-8200418 +(353)-19014670

Silicone Dispersion

Relevant Identified Uses of the Substance or Mixture and Uses Advised Against

: +1 703-527-3887 CHEMTREC (International and Maritime), 800-424-9300

For professional use only.

Labelling According to Regulation (EC) No. 1272/2008 [CLP]

**SECTION 2: Hazards Identification** 

Full text of hazard classes and H-statements : see section 16

Classification of the Substance or Mixture

Classification According to Regulation (EC) No. 1272/2008







Safety Data Sheet According to Regulation (EC) No. 1907/

According to Regulation (EC) No. 1907/2006 (REACH) with its c	imendment Regulation (EU) 2015/830
	P233 - Keep container tightly closed.
	P240 - Ground and bond container and receiving equipment.
	P241 - Use explosion-proof electrical/ventilating/lighting
	equipment.
	P242 - Use non-sparking tools.
	P243 - Take action to prevent static discharges.
	P261 - Avoid breathing vapours, mist, spray.
	P264 - Wash hands, forearms and face thoroughly after
	handling.
	P271 - Use only outdoors or in a well-ventilated area.
	P280 - Wear protective gloves/protective clothing/eye
	protection/face protection/hearing protection.
	P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all
	contaminated clothing. Rinse skin with water .
	P304+P340 - IF INHALED: Remove person to fresh air and keep
	comfortable for breathing.
	P305+P351+P338 - IF IN EYES: Rinse cautiously with water for
	several minutes. Remove contact lenses, if present and easy to
	do. Continue rinsing.
	P312 - Call a POISON CENTRE or doctor if you feel unwell.
	P337+P313 - If eye irritation persists: Get medical
	advice/attention.
	P370+P378 - In case of fire: Use media other than water to
	extinguish.
	P403+P235 - Store in a well-ventilated place. Keep cool.
	P405 - Store locked up.
	P501 - Dispose of contents/container to hazardous or special
	waste collection point, in accordance with local, regional,
	national and/or international regulation.
EUH-statements	EUH066 - Repeated exposure may cause skin dryness or
	cracking.
2.3. Other Hazards	CIUCNIIY.
Other Hazards Not Contributing	Exposure may aggravate pre-existing eye, skin, or respiratory

# SECTION 3: Composition/Information on Ingredients

conditions.

## 3.1. Substances

to the Classification

Not applicable

### 3.2. Mixtures

Name	Product Identifier	%	Classification According to Regulation (EC) No. 1272/2008
Ethyl acetate	(CAS-No.) 141-78-6 (EC-No.) 205-500-4 (EC Index-No.) 607-022-00-5	30 - 50	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336

Full text of H-statements: see section 16

Safety Data Sheet According to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

## **SECTION 4: First Aid Measures**

## 4.1. Description of First-aid Measures

First-Aid Measures General	Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-Aid Measures After	When symptoms occur: go into open air and ventilate
Inhalation	suspected area. Obtain medical attention if breathing difficulty persists.
First-Aid Measures After Skin	Immediately drench affected area with water for at least 15
Contact	minutes. Obtain medical attention if irritation develops or persists. Immediately remove contaminated clothing.
First-Aid Measures After Eye	Immediately rinse with water for at least 15 minutes. Remove
Contact	contact lenses, if present and easy to do. Continue rinsing.
Connact	Obtain medical attention if irritation develops or persists.
First-Aid Measures After	Rinse mouth. Do NOT induce vomiting. Obtain medical
Ingestion	attention.
5	ms and Effects Both Acute and Delayed
	-
Symptoms/Effects	Causes serious eye irritation. May cause drowsiness and dizziness.
Symptoms/Effects After	High concentrations may cause central nervous system
Inhalation	depression such as dizziness, vomiting, numbness, drowsiness,
	headache, and similar narcotic symptoms.
Symptoms/Effects After Skin	Prolonged exposure may cause skin irritation.
Contact	
Symptoms/Effects After Eye	Contact causes severe irritation with redness and swelling of the
Contact	conjunctiva.
Symptoms/Effects After Ingestion	Ingestion may cause adverse effects.
Chronic Symptoms	Repeated exposure may cause skin dryness or cracking. Repeated or prolonged exposure to high levels may affect the liver and kidneys.

## 4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention. If medical advice is needed, have product container or label at hand.

## **SECTION 5: Firefighting Measures**

## 5.1. Extinguishing Media

Suitable Extinguishing Media	Dry chemical powder, alcohol-resistant foam, carbon dioxide (CO <sub>2</sub> ). Water may be ineffective but water should be used to keep fire-exposed container cool.
Unsuitable Extinguishing Media	Do not use a heavy water stream. A heavy water stream may spread burning liquid.
5.2. Special Hazards Arising	From the Substance or Mixture
Fire Hazard	Highly flammable liquid and vapour. Vapours are heavier than
	air and may travel considerable distance to an ignition source
	and flash back to source of vapours.
Explosion Hazard	May form flammable or explosive vapour-air mixture. Heating will cause rise in pressure with risk of bursting.
5.2. Special Hazards Arising I Fire Hazard	spread burning liquid. From the Substance or Mixture Highly flammable liquid and vapour. Vapours are heavier than air and may travel considerable distance to an ignition source and flash back to source of vapours. May form flammable or explosive vapour-air mixture. Heating

Safety Data Sheet According to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Reactivity	Reacts violently with strong oxidisers. Increased risk of fire or explosion.
Hazardous Decomposition Products in Case of Fire	Carbon oxides (CO, CO <sub>2</sub> ). Silicon oxides.
5.3. Advice for Firefighters	
Precautionary Measures Fire	Exercise caution when fighting any chemical fire.
Firefighting Instructions	Use water spray or fog for cooling exposed containers. In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion.
Protection During Firefighting	Do not enter fire area without proper protective equipment, including respiratory protection.

## **SECTION 6: Accidental Release Measures**

### 6.1. Personal Precautions, Protective Equipment and Emergency Procedures

**General Measures** 

Avoid breathing (vapor, mist, spray). Avoid all contact with skin, eyes, or clothing. Do not get in eyes, on skin, or on clothing. Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking. Use special care to avoid static electric charges.

### 6.1.1. For Non-Emergency Personnel

Protective Equipment	Use appropriate personal protective equipment (PPE).
Emergency Procedures	Evacuate unnecessary personnel. Stop leak if safe to do so.
6.1.2. For Emergency Responders	
Protective Equipment	Equip cleanup crew with proper protection.
Emergency Procedures	Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit. Eliminate ignition sources first, then ventilate the area.

### 6.2. Environmental Precautions

Prevent entry to sewers and public waters.

### 6.3. Methods and Materials for Containment and Cleaning Up

For Containment

Methods For Cleaning Up

Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. As an immediate precautionary measure, isolate spill or leak area in all directions. Clean up spills immediately and dispose of waste safely. Absorb and/or contain spill with inert material. Do not take up in combustible material such as: saw dust or cellulosic material. Transfer spilled material to a suitable container for disposal. Use only non-sparking tools. Contact competent authorities after a spill.

### 6.4. Reference to Other Sections

See Section 8 for exposure controls and personal protection and Section 13 for disposal considerations.

## SECTION 7: Handling And Storage

### 7.1. Precautions for Safe Handling

Additional Hazards When	Handle empty containers with care because residual vapours
Processed	are flammable.

Safety Data Sheet According to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Precautions for Safe Handling	Avoid contact with skin, eyes and clothing. Avoid breathing vapors, mist, spray. Take precautionary measures against static discharge. Use only non-sparking tools. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.
Hygiene Measures	Handle in accordance with good industrial hygiene and safety procedures.
7.2. Conditions for Safe Storag	ge, Including Any Incompatibilities
Technical Measures	Comply with applicable regulations. Take action to prevent static discharges. Ground and bond container and receiving equipment. Use explosion-proof electrical, ventilating, and lighting equipment.
Storage Conditions	Store in a dry, cool place. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials. Store locked up/in a secure area. Store in a well- ventilated place. Keep container tightly closed. Keep in fireproof place.
Incompatible Materials	Strong acids, strong bases, strong oxidizers. Attacks some forms of plastics, rubber, and coatings. Water.
<b>7.3. Specific End Use(S)</b> For professional use only.	

## **SECTION 8: Exposure Controls/Personal Protection**

### 8.1. **Control Parameters**

78-6)		
IOEL TWA	734 mg/m³	
IOEL TWA [ppm]	200 ppm	
IOEL STEL	1468 mg/m <sup>3</sup>	
IOEL STEL [ppm]	400 ppm	
MAK (OEL TWA)	734 mg/m³	
MAK (OEL TWA) [ppm]	200 ppm	
MAK (OEL STEL)	1468 mg/m <sup>3</sup>	
MAK (OEL STEL) [ppm]	400 ppm	
OEL TWA	734 mg/m³	
OEL TWA [ppm]	200 ppm	
OEL STEL	1468 mg/m <sup>3</sup>	
OEL STEL [ppm]	400 ppm	
OEL TWA	734 mg/m³	
OEL TWA [ppm]	200 ppm	
OEL STEL	1468 mg/m <sup>3</sup>	
OEL STEL [ppm]	400 ppm	
GVI (OEL TWA) [1]	734 mg/m³	
GVI (OEL TWA) [2]	200 ppm	
KGVI (OEL STEL)	1468 mg/m <sup>3</sup>	
KGVI (OEL STEL) [ppm]	400 ppm	
OEL TWA	734 mg/m³	
OEL TWA [ppm]	200 ppm	
	IOEL TWA IOEL TWA [ppm] IOEL STEL IOEL STEL [ppm] MAK (OEL TWA) MAK (OEL TWA) [ppm] MAK (OEL STEL) MAK (OEL STEL) [ppm] OEL TWA OEL TWA [ppm] OEL STEL OEL STEL [ppm] OEL STEL [ppm] OEL STEL OEL STEL [ppm] GVI (OEL TWA) [1] GVI (OEL TWA) [1] GVI (OEL TWA) [2] KGVI (OEL STEL) [ppm] OEL TWA	IOEL TWA         734 mg/m³           IOEL TWA [ppm]         200 ppm           IOEL STEL         1468 mg/m³           IOEL STEL [ppm]         400 ppm           MAK (OEL TWA)         734 mg/m³           MAK (OEL TWA)         734 mg/m³           MAK (OEL TWA) [ppm]         200 ppm           MAK (OEL STEL)         1468 mg/m³           MAK (OEL STEL)         1468 mg/m³           OEL TWA         734 mg/m³           OEL TWA [ppm]         200 ppm           OEL STEL         1468 mg/m³           OEL STEL [ppm]         400 ppm           OEL TWA         734 mg/m³           OEL TWA         734 mg/m³           OEL STEL [ppm]         400 ppm           OEL STEL [ppm]         400 ppm           GVI (OEL TWA) [1]         734 mg/m³           GVI (OEL TWA) [2]         200 ppm           GVI (OEL TWA) [2]         200 ppm           KGVI (OEL STEL)         1468 mg/m³           KGVI (OEL STEL)         1468 mg/m³           KGVI (OEL STEL) [ppm]         400 ppm

Safety Data Sheet According to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

	2006 (REACH) with its amenament regulation (EU) 2015/8	
Cyprus	OEL STEL	1468 mg/m <sup>3</sup>
Cyprus	OEL STEL [ppm]	400 ppm
Czech Republic	PEL (OEL TWA)	700 mg/m <sup>3</sup>
Denmark	OEL TWA [1]	540 mg/m <sup>3</sup>
Denmark	OEL TWA [2]	150 ppm
Estonia	OEL TWA	500 mg/m <sup>3</sup>
Estonia	OEL TWA [ppm]	150 ppm
Estonia	OEL STEL	1100 mg/m³
Estonia	OEL STEL [ppm]	300 ppm
Finland	HTP (OEL TWA) [1]	730 mg/m³
Finland	HTP (OEL TWA) [2]	200 ppm
Finland	HTP (OEL STEL)	1470 mg/m <sup>3</sup>
Finland	HTP (OEL STEL) [ppm]	400 ppm
France	VME (OEL TWA)	1400 mg/m <sup>3</sup>
France	VME (OEL TWA) [ppm]	400 ppm
Germany	AGW (OEL TWA) [1]	730 mg/m³ (the risk of damage to the
		embryo or fetus can be excluded when
		AGW and BGW values are observed)
Germany	AGW (OEL TWA) [2]	200 ppm (the risk of damage to the
		embryo or fetus can be excluded when
		AGW and BGW values are observed)
Gibraltar	OEL TWA	200 mg/m <sup>3</sup>
Gibraltar	OEL TWA [ppm]	734 ppm
Gibraltar	OEL STEL	400 mg/m <sup>3</sup>
Gibraltar	OEL STEL [ppm]	1468 ppm
Greece	OEL TWA	734 mg/m <sup>3</sup>
Greece	OEL TWA [ppm]	200 ppm
Greece	OEL STEL	1468 mg/m <sup>3</sup>
Greece	OEL STEL [ppm]	400 ppm
Hungary	AK (OEL TWA)	734 mg/m <sup>3</sup>
Hungary	CK (OEL STEL)	1468 mg/m <sup>3</sup>
Hungary	Chemical category	Sensitizer
Ireland	OEL TWA [1]	734 mg/m <sup>3</sup>
Ireland	OEL TWA [2]	200 ppm
Ireland	OEL STEL	1468 mg/m <sup>3</sup>
Ireland	OEL STEL [ppm]	400 ppm
Italy	OEL TWA	734 mg/m <sup>3</sup>
Italy	OEL TWA [ppm]	200 ppm
Italy	OEL STEL	1468 mg/m <sup>3</sup>
Italy	OEL STEL [ppm]	400 ppm
Latvia	OEL TWA	200 mg/m <sup>3</sup>
Latvia	OEL TWA [ppm]	54 ppm
Lithuania	IPRV (OEL TWA)	500 mg/m <sup>3</sup>
Lithuania	IPRV (OEL TWA) [ppm]	150 ppm
Lithuania	NRV (OEL C)	1100 mg/m³
29/06/2021	EN (English)	6/12

Safety Data Sheet According to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Lithuania	REACH) with its amendment Regulation (EU) 2015/830 NRV (OEL C) [ppm]	300 ppm
Luxembourg	OEL STEL	1468 mg/m <sup>3</sup>
Luxembourg	OEL STEL [ppm]	400 ppm
Malta	OEL TWA	
Malta		734 mg/m <sup>3</sup>
	OEL TWA [ppm]	200 ppm
Malta	OEL STEL	1468 mg/m <sup>3</sup>
Malta	OEL STEL [ppm]	400 ppm
Netherlands	MAC-TGG (OEL TWA)	734 mg/m <sup>3</sup>
Netherlands	MAC-15 (OEL STEL)	1468 mg/m <sup>3</sup>
Norway	Grenseverdi (OEL TWA) [1]	734 mg/m³
Norway	Grenseverdi (OEL TWA) [2]	200 ppm
Norway	Korttidsverdi (OEL STEL)	1468 mg/m <sup>3</sup> (value from the regulation)
Norway	Korttidsverdi (OEL STEL) [ppm]	400 ppm (value from the regulation)
Poland	NDS (OEL TWA)	734 mg/m³
Poland	NDSCh (OEL STEL)	1468 mg/m <sup>3</sup>
Portugal	OEL TWA	734 mg/m³ (indicative limit value)
Portugal	OEL TWA [ppm]	200 ppm (indicative limit value)
Portugal	OEL STEL	1468 mg/m³ (indicative limit value)
Portugal	OEL STEL [ppm]	400 ppm (indicative limit value)
Romania	OEL TWA	400 mg/m <sup>3</sup>
Romania	OEL TWA [ppm]	111 ppm
Romania	OEL STEL	500 mg/m <sup>3</sup>
Romania	OEL STEL [ppm]	139 ppm
Slovakia	NPHV (OEL TWA) [1]	734 mg/m <sup>3</sup>
Slovakia	NPHV (OEL TWA) [2]	200 ppm
Slovakia	NPHV (OEL C)	1100 mg/m <sup>3</sup>
Slovenia	OEL TWA	734 mg/m <sup>3</sup>
Slovenia	OEL TWA [ppm]	200 ppm
Slovenia	OEL STEL	1468 mg/m <sup>3</sup>
Slovenia	OEL STEL [ppm]	400 ppm
Spain	VLA-ED (OEL TWA) [1]	734 mg/m <sup>3</sup>
Spain	VLA-ED (OEL TWA) [2]	200 ppm
Spain	VLA-EC (OEL STEL)	1468 mg/m <sup>3</sup>
Spain	VLA-EC (OEL STEL) [ppm]	400 ppm
Sweden	NGV (OEL TWA)	550 mg/m <sup>3</sup>
Sweden	NGV (OEL TWA) [ppm]	150 ppm
Sweden	KTV (OEL STEL)	1100 mg/m <sup>3</sup>
Sweden	KTV (OEL STEL) [ppm]	300 ppm
Switzerland	KZGW (OEL STEL)	1460 mg/m <sup>3</sup>
Switzerland	KZGW (OEL STEL) [ppm]	400 ppm
Switzerland	MAK (OEL TWA) [1]	730 mg/m <sup>3</sup>
Switzerland	MAK (OEL TWA) [2]	200 ppm
United Kingdom	WELTWA (OELTWA) [1]	734 mg/m <sup>3</sup>
United Kingdom	WEL TWA (OEL TWA) [2]	200 ppm

Safety Data Sheet

According to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

United Kingdom	WEL STEL (OEL STEL)	1468 mg/m <sup>3</sup>
United Kingdom	WEL STEL (OEL STEL) [ppm]	400 ppm

## 8.2. Exposure Controls

Appropriate Engineering Controls Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure adequate ventilation, especially in confined areas. Ensure all national/local regulations are observed. Gas detectors should be used when flammable gases or vapors may be released. Proper grounding procedures to avoid static electricity should be followed. Use explosion-proof equipment. Gloves. Protective clothing. Protective goggles. Insufficient ventilation: wear respiratory protection.



Materials for Protective Clothing

Personal Protective Equipment

Hand Protection Eye Protection Skin and Body Protection Respiratory Protection Chemically resistant materials and fabrics. Wear fire/flame resistant/retardant clothing.
Wear protective gloves.
Chemical safety goggles.
Wear suitable protective clothing.
If exposure limits are exceeded or irritation is experienced, approved respiratory protection should be worn. In case of inadequate ventilation, oxygen deficient atmosphere, or where exposure levels are not known wear approved respiratory protection.

Other Information

When using, do not eat, drink or smoke.

## **SECTION 9: Physical and Chemical Hazards**

## 9.1. Information on Basic Physical and Chemical Properties

Physical State	Liquid
Colour	Colourless
Odour	Ester like
Odour Threshold	No data available
рН	No data available
Evaporation Rate	No data available
Melting Point	No data available
Freezing Point	No data available
Boiling Point	77 – 78 °C (171 – 172 °F)
Flash Point	-4 °C (25 °F)
Auto-Ignition Temperature	No data available
Decomposition Temperature	No data available
Flammability (Solid, Gas)	Not applicable
Vapour Pressure	No data available
Relative Vapour Density At 20 °C	No data available
Relative Density	< 1 (water = 1)
Solubility	No data available
Partition Coefficient n-Octanol/Water	No data available
Viscosity, Kinematic	No data available
Viscosity, Dynamic	No data available
Explosive Properties	No data available

Safety Data Sheet According to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Oxidising Properties Explosive Limits No data available No data available

## 9.2. Other Information

No additional information available

## SECTION 10: Stability and Reactivity

## 10.1. Reactivity

Reacts violently with strong oxidisers. Increased risk of fire or explosion.

## 10.2. Chemical Stability

Highly flammable liquid and vapour. May form flammable or explosive vapour-air mixture.

## 10.3. Possibility Of Hazardous Reactions

Hazardous polymerization will not occur.

## 10.4. Conditions To Avoid

Direct sunlight, extremely high or low temperatures, heat, hot surfaces, sparks, open flames, incompatible materials, and other ignition sources.

## 10.5. Incompatible Materials

Strong acids, strong bases, strong oxidizers. Attacks some forms of plastics, rubber, and coatings. Water.

## 10.6. Hazardous Decomposition Products

Decomposes slowly on exposure to water to form acetic acid and ethanol.

## **SECTION 11: Toxicological Information**

11.1. Information On Toxicological Effects Acute Toxicity Not classified (Based on available data, the classification criteria are not met) Ethyl acetate (141-78-6) LD50 Oral Rat 5620 mg/kg ID50 Oral 4940 mg/kg LD50 Dermal Rabbit > 18000 mg/kg LC50 Inhalation Rat 4000 ppm/4h LC50 Inhalation Rat > 7348 mg/l/4h (calculated off of 6hr test results) Skin Corrosion/Irritation Not classified (Based on available data, the classification criteria are not met) Eye Damage/Irritation Causes serious eye irritation. Respiratory or Skin Sensitization Not classified (Based on available data, the classification criteria are not met) Germ Cell Mutagenicity Not classified (Based on available data, the classification criteria are not met) Not classified (Based on available data, the classification Carcinogenicity criteria are not met) **Reproductive Toxicity** Not classified (Based on available data, the classification criteria are not met) Specific Target Organ Toxicity (Single May cause drowsiness or dizziness. Exposure) Specific Target Organ Toxicity (Repeated Not classified (Based on available data, the classification criteria are not met) Exposure)

Not classified (Based on available data, the classification

Aspiration Hazard

criteria are not met)

Safety Data Sheet According to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

## **SECTION 12: Ecological Information**

## 12.1. Toxicity

Ecology - General	Not classified.
Ethyl acetate (141-78-6)	
LC50 Fish 1	220 – 250 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 - Crustacea [1]	560 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
LC50 Fish 2	484 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [flow-through])

## 12.2. Persistence and Degradability

MED-1356		
Persistence and Degradability	Not established.	
12.3. Bioaccumulative Potential		
MED-1356		
Bioaccumulative potential	Not established.	
Ethyl acetate (141-78-6)		
BCF Fish 1	30	
Partition coefficient n- octanol/water (Log Pow)	0,6	

## 12.4. Mobility in Soil

No additional information available

## 12.5. Results of PBT and vPvB assessment

MED-1356	
PBT: not relevant – no registration required	
vPvB: not relevant – no registration required	
124 Other Adverse Effects	

### 12.6. Other Adverse Effects

Other Information

Avoid release to the environment.

## **SECTION 13: Disposal Considerations**

## 13.1. Waste Treatment Methods

Product/Packaging Disposal	Dispose of contents/container in accordance with local,
Recommendations	regional, national, and international regulations.
Additional Information	Handle empty containers with care because residual vapours are flammable.
Ecology - Waste Materials	Avoid release to the environment.

## **SECTION 14: Transport Information**

The shipping description(s) stated herein were prepared in accordance with certain assumptions at the time the SDS was authored, and can vary based on a number of variables that may or may not have been known at the time the SDS was issued.

In accordance with ADR / RID / IMDG /	/ IATA / ADN

ADR	IMDG	IATA	ADN	RID	
14.1. UN Nun	nber				
1173	1173	1173	1173	1173	
29/06/2021		EN (English)			10/12

Safety Data Sheet

According to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

ADR	IMDG	IATA	ADN	RID
14.2. UN Proper S	Shipping Name			
ETHYL ACETATE	ETHYL ACETATE	ETHYL ACETATE	ETHYL ACETATE	ETHYL ACETATE
(Solution)	(Solution)	(Solution)	(Solution)	(Solution)
14.3. Transport H	14.3. Transport Hazard Class(Es)			
3	3	3	3	3
14.4. Packing Gr	oup			
	II		II	II
14.5. Environmental Hazards				
Dangerous for	Dangerous for	Dangerous for	Dangerous for	Dangerous for
the environment :	the environment :	the environment :	the environment :	the environment :
No	No	No	No	No
	Marine pollutant :			
	No			
447 6 115				

## 14.6. Special Precautions For User

No additional information available

**14.7. Transport in Bulk According to Annex II of MARPOL and The IBC Code** Not applicable

## **SECTION 15: Regulatory Information**

# 15.1. Safety, Health and Environmental Regulations/Legislation Specific for the Substance or Mixture

### 15.1.1. EU-Regulations

Contains no substance on the REACH candidate list Contains no REACH Annex XIV substances

### 15.1.2. National Regulations

No additional information available

### 15.2. Chemical Safety Assessment

No chemical safety assessment has been carried out

## **SECTION 16: Other Information**

### **Indication of Changes**

Section	Section Header	Change	Date Changed
1	Identification of the Substance/mixture and	Modified	29/06/2021
	of the Company/Undertaking		

Date of Preparation or Latest Revision Data Sources

## 29/06/2021

Information and data obtained and used in the authoring of this safety data sheet could come from database subscriptions, official government regulatory body websites, product/ingredient manufacturer or supplier specific information, and/or resources that include substance specific data and classifications according to GHS or their subsequent adoption of GHS.

Safety Data Sheet

According to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Other Information

According to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Full Text of H- and EUH-statements:

Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
H225	Highly flammable liquid and vapour.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
EUH066	Repeated exposure may cause skin dryness or cracking.

## Abbreviations and Acronyms

ACGIH - American Conference of Governmental Industrial Hygienists NDS - Naiwyzsze Dopuszczalne Stezenie ADN – European Agreement Concerning the International Carriage of Dangerous NDSCh - Najwyzsze Dopuszczalne Stezenie Chwilowe Goods by Inland Waterways NDSP - Najwyzsze Dopuszczalne Stezenie Pulapowe NOAEL - No-Observed Adverse Effect Level ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road NOEC - No-Observed Effect Concentration ATE - Acute Toxicity Estimate NRD - Nevirsytings Ribinis Dydis BCF - Bioconcentration Factor NTP - National Toxicology Program BEI - Biological Exposure Indices (BEI) OEL - Occupational Exposure Limits BOD - Biochemical Oxygen Demand PBT - Persistent, Bioaccumulative and Toxic CAS No. - Chemical Abstracts Service Number PEL - Permissible Exposure Limit CLP - Classification, Labeling and Packaging Regulation (EC) No 1272/2008 pH – Potential Hydrogen COD - Chemical Oxygen Demand REACH – Registration, Evaluation, Authorisation, and Restriction of Chemicals EC – European Community EC50 - Median Effective Concentration RID - Regulations Concerning the International Carriage of Dangerous Goods by Rail SADT - Self Accelerating Decomposition Temperature - European Economic Community SDS - Safety Data Sheet EINECS – European Inventory of Existing Commercial Chemical Substances EmS-No. (Fire) - IMDG Emergency Schedule Fire STEL - Short Term Exposure Limit STOT - Specific Target Organ Toxicity EmS-No. (Spillage) - IMDG Emergency Schedule Spillage TA-Luft - Technische Anleitung zur Reinhaltung der Luft FU - Furopean Union TEL TRK – Technical Guidance Concentrations ErC50 - EC50 in Terms of Reduction Growth Rate ThOD – Theoretical Oxygen Demand GHS – Globally Harmonized System of Classification and Labeling of Chemicals TLM - Median Tolerance Limit TLV - Threshold Limit Value IARC - International Agency for Research on Cancer IATA - International Air Transport Association TPRD - Trumpalaikio Poveikio Ribinis Dydis IBC Code - International Bulk Chemical Code TRGS 510 - Technische Regel für Gefahrstoffe 510 - Lagerung von Gefahrstoffen in ortsbeweglichen Behältern IMDG - International Maritime Dangerous Goods IPRV - Ilgalaikio Poveikio Ribinis Dydis TRGS 552 – Technische Regeln für Gefahrstoffe - N-Nitrosamine IOELV – Indicative Occupational Exposure Limit Value LC50 - Median Lethal Concentration TRGS 900 - Technische Regel für Gefahrstoffe 900 – Arbeitsplatzgrenzwerte TRGS 903 - Technische Regel für Gefahrstoffe 903 - Biologische Grenzwerte LD50 - Median Lethal Dose TSCA - Toxic Substances Control Act LOAEL - Lowest Observed Adverse Effect Level TWA - Time Weighted Average LOEC - Lowest-Observed-Effect Concentration - Volatile Organic Compounds Log Koc - Soil Organic Carbon-water Partitioning Coefficient Log Kow - Octanol/water Partition Coefficient VLA-EC - Valor Límite Ambiental Exposición de Corta Duración VLA-ED - Valor Límite Ambiental Exposición Diaria Log Pow - Ratio of the equilibrium concentration (C) of a dissolved substance in a two VLE – Valeur Limite D'exposition phase system consisting of two largely immiscible solvents, in this case octanol and VME - Valeur Limite De Movenne Exposition vPvB - Very Persistent and Very Bioaccumulative water WEL – Workplace Exposure Limit MAK - Maximum Workplace Concentration/Maximum Permissible Concentration MARPOL - International Convention for the Prevention of Pollution WGK - Wassergefährdungsklasse

Nusil EU GHS SDS

The information provided in this Safety Data Sheet (SDS) was prepared based on data believed to be accurate as of the date of this SDS. TO THE GREATEST EXTENT PERMITTED BY LAW, NUSIL TECHNOLOGY LLC AND ITS AFFILIATED COMPANIES ("NUSIL") EXPRESSLYDISCLAIMS ANY AND ALL REPRESENTATIONS AND WARRANTIES REGARDING THE INFORMATION CONTAINED HEREIN INCLUDING, WITHOUT LIMITATION, AS TO ACCURACY, COMPLETENESS, FITNESS FOR PURPOSE OR USE, MERCHANTABILITY, NON-INFRINGEMENT, PERFORMANCE, SAFETY, SUITABILITY AND STABILITY. This SDS is intended as a guide to the appropriate use, handling, storage and disposal of the product to which it relates by properly trained personnel, and is not intended to be comprehensive. Users of NuSil's products are advised to perform their own tests and to exercise their own judgment to determine the safety, suitability and appropriate use, handling, storage and disposal of each product and product combination for their own purposes and uses. TO THE GREATEST EXTENT PERMITTED BY LAW, NUSIL DISCLAIMS LIABILITY FOR, AND BY USING NUSIL'S PRODUCTS PURCHASER AGREES THAT UNDER NO CIRCUMSTANCES SHALL NUSIL BE LIABLE FOR, SPECIAL, INDIRECT, INCIDENTAL, PUNITIVE OR CONSEQUENTIAL DAMAGES OF ANY TYPE OR KIND, INCLUDING WITHOUT LIMITATION, FOR LOSS OF PROFITS, REPUTATIONAL DAMAGE, PRODUCT RECALL OR BUSINESS INTERRUPTION.