### SECTION 1: Identification of the Substance/mixture and of the Company/Undertaking

#### **Product Identifier** 1.1.

Product form **Product Name Svnonvms** 

Mixture R-1008-6 Silicone Ink

#### Relevant Identified Uses of the Substance or Mixture and Uses Advised Against 1.2.

1.2.1. Relevant Identified Uses Use of the Substance/Mixture

For professional use only.

#### 1.2.2. Uses Advised Against

No additional information available

#### Details of the Supplier of the Safety Data Sheet 1.3.

NuSil Technology Europe 1198 Avenue Maurice Donat Le Natura Bt. 2 06250 Mougins France +33 4 92 96 93 31 ehs@nusil.com www.nusil.com

#### 1.4. **Emergency Telephone Number**

**Emergency Number** 

: 800-424-9300 CHEMTREC (in US); +1 703-527-3887 CHEMTREC (International and Maritime) +(44)-870-8200418 +(353)-19014670)

### **SECTION 2: Hazards Identification**

#### Classification of the Substance or Mixture 2.1.

### Classification According to Regulation (EC) No. 1272/2008 [CLP]

Flam. Lia. 3 H226 Skin Irrit. 2 H315 Eve Irrit. 2 H319 Skin Sens. 1 H317 STOT SE 3 H335 STOT RE 2 H373 Asp. Tox. 1 H304

Full text of hazard classes and H-statements : see section 16

#### 2.2. Label Elements

Labelling According to Regulation (EC) No. 1272/2008 [CLP]

Hazard Pictograms (CLP)

Signal Word (CLP)

Danger

GHS07

GHS08

GHS02



Version: 4.0

Safety Data Sheet

According to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 2-Butanone, O,O',O''-(methylsilylidyne)trioxime; Dibutyltin Hazardous Ingredients dilaurate; Reaction mass of ethylbenzene and xylene Hazard Statements (CLP) H226 - Flammable liquid and vapour. H304 - May be fatal if swallowed and enters airways. H315 - Causes skin irritation. H317 - May cause an allergic skin reaction. H319 - Causes serious eye irritation. H335 - May cause respiratory irritation. H373 - May cause damage to organs (blood) through prolonged or repeated exposure (oral). Precautionary Statements (CLP) P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P233 - Keep container tightly closed. P240 - Ground and bond container and receiving equipment. P241 - Use explosion-proof electrical, ventilating, and lighting equipment. P242 - Use non-sparking tools. P243 - Take action to prevent static discharges. P260 - Do not breathe mist, spray, vapours P264 - Wash hands, forearms, and exposed areas thoroughly after handling P270 - Do not eat, drink or smoke when using this product P271 - Use only outdoors or in a well-ventilated area. P272 - Contaminated work clothing should not be allowed out of the workplace. P280 - Wear eye protection, protective clothing, protective gloves P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor P302+P352 - IF ON SKIN: Wash with plenty of water P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P312 - Call a POISON CENTRE or doctor if you feel unwell. P321 - Specific treatment (see Section 4 on this SDS) P330 - Rinse mouth. P331 - Do NOT induce vomiting. P332+P313 - If skin irritation occurs: Get medical advice/attention. P333+P313 - If skin irritation or rash occurs: Get medical advice/attention. P337+P313 - If eye irritation persists: Get medical advice/attention. P362+P364 - Take off contaminated clothing and wash it before reuse. P370+P378 - In case of fire: Use appropriate media (see section 5) to extinguish P403+P233+P235 - Store in a well-ventilated place. Keep

container tightly closed. Keep cool. P405 - Store locked up. P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

#### 2.3. Other Hazards

Other Hazards Not Contributing to the Classification

Exposure may aggravate pre-existing eye, skin, or respiratory conditions.

### **SECTION 3: Composition/Information on Ingredients**

#### 3.1. Substances

Not applicable

#### 3.2. Mixtures

Name	Product Identifier	%	Classification According to Regulation (EC) No. 1272/2008 [CLP]
Chromium oxide (Cr2O3)	(CAS-No.) 1308-38-9 (EC-No.) 215-160-9	20 - 30	Not classified
Reaction mass of ethylbenzene and xylene	(CAS-No.) Not Applicable (REACH Registration No.) 01-2119539452-40-0053 (EC-No.) 905-588-0	10 - 30	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation:vapour), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304
2-Butanone, O,O',O''- (methylsilylidyne)trioxime	(CAS-No.) 22984-54-9 (EC-No.) 245-366-4	< 15	Eye Irrit. 2, H319 Skin Sens. 1B, H317 STOT RE 2, H373
DibutyItin dilaurate	(CAS-No.) 77-58-7 (EC-No.) 201-039-8 (EC Index-No.) 050-030-00-3	< 0.3	Skin Corr. 1C, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 Muta. 2, H341 Repr. 1B, H360 STOT SE 1, H370 STOT RE 1, H372 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

Full text of H-statements: see section 16

### SECTION 4: First Aid Measures

#### 4.1. Description of First-aid Measures

First-Aid Measures General

Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

Safety Data Sheet According to Regulation (EC) No. 190

ccording to Regulation (EC) No. 1907/2006 (REACH) with its a	mendment Regulation (EU) 2015/830
First-Aid Measures After	When symptoms occur: go into open air and ventilate
Inhalation	suspected area. Obtain medical attention if breathing difficulty
	persists.
First-Aid Measures After Skin	Immediately remove contaminated clothing. Obtain medical
Contact	attention if irritation/rash develops or persists. Immediately
	drench affected area with water for at least 15 minutes.
First-Aid Measures After Eye	Immediately rinse with water for at least 15 minutes. Remove
Contact	contact lenses, if present and easy to do. Continue rinsing.
	Obtain medical attention.
First-Aid Measures After	Do NOT induce vomiting. Rinse mouth. Immediately call a
Ingestion	POISON CENTER or doctor/physician.
4.2. Most Important Sympton	ns and Effects Both Acute and Delayed
Symptoms/Effects	May cause respiratory irritation. May cause damage to organs
	through prolonged or repeated exposure. Skin sensitisation.
	Causes skin irritation. Causes serious eye irritation. May be fatal
	if swallowed and enters airways.
Symptoms/Effects After	May cause irritation to the respiratory tract, sneezing, coughing,
Inhalation	burning sensation of throat with constricting sensation of the
	larynx and difficulty in breathing
Symptoms/Effects After Skin	May cause an allergic skin reaction. Redness, pain, swelling,
Contact	itching, burning, dryness, and dermatitis.
Symptoms/Effects After Eye	Contact causes severe irritation with redness and swelling of the
Contact	conjunctiva.
Symptoms/Effects After	Aspiration into the lungs can occur during ingestion or vomiting
Ingestion	and may cause lung injury.
Chronic Symptoms	May cause damage to organs (blood) through prolonged or
	repeated exposure (Oral).
13 Indication of Any Immed	diate Medical Attention and Special Treatment Needed

### 4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention. If medical advice is needed, have product container or label at hand.

### **SECTION 5: Firefighting Measures**

### 5.1. Extinguishing Media

Suitable Extinguishing Media	Dry chemical powder, alcohol-resistant foam, carbon dioxide (CO <sub>2</sub> ). Water may be ineffective but water should be used to
Unsuitable Extinguishing Media	keep fire-exposed container cool. Do not use a heavy water stream. A heavy water stream may spread burning liquid.
5.2. Special Hazards Arising Fro	om the Substance or Mixture
Fire Hazard	Flammable liquid and vapour.
Explosion Hazard	May form flammable or explosive vapour-air mixture.
Reactivity	Reacts violently with strong oxidisers. Increased risk of fire or explosion.
Hazardous Decomposition Products in Case of Fire	Silicon oxides. Carbon oxides (CO, CO <sub>2</sub> ). Metal oxides. Oxides of tin.
5.3. Advice for Firefighters	
Precautionary Measures Fire Firefighting Instructions	Exercise caution when fighting any chemical fire. Use water spray or fog for cooling exposed containers. In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion.

Safety Data Sheet

According to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Protection During Firefighting	Do not enter fire area without proper protective equipment,
	including respiratory protection.
Other Information	Do not allow run-off from fire fighting to enter drains or water
	courses.

### **SECTION 6: Accidental Release Measures**

#### 6.1. Personal Precautions, Protective Equipment and Emergency Procedures

General MeasuresDo not get in eyes, on skin, or on clothing. Keep away from<br/>heat, hot surfaces, sparks, open flames, and other ignition<br/>sources. No smoking. Use special care to avoid static electric<br/>charges. Do not breathe vapor, mist or spray.6.1.1. For Non-Emergency Personnel<br/>Protective Equipment<br/>Emergency ProceduresUse appropriate personal protective equipment (PPE).<br/>Evacuate unnecessary personnel. Stop leak if safe to do so.6.1.2. For Emergency RespondersDo not get in eyes, on skin, or on clothing. Keep away from<br/>heat, hot surfaces, sparks, open flames, and other ignition<br/>sources. No smoking. Use special care to avoid static electric<br/>charges. Do not breathe vapor, mist or spray.

Protective Equipment Emergency Procedures	Equip cleanup crew with proper protection. Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit. Ventilate area.
	Eliminate ignition sources.

#### 6.2. Environmental Precautions

Prevent entry to sewers and public waters. Avoid release to the environment.

#### 6.3. Methods and Materials for Containment and Cleaning Up

For Containment	Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. As an immediate precautionary measure, isolate spill or leak area in all directions.
Methods For Cleaning Up	Clean up spills immediately and dispose of waste safely. Transfer spilled material to a suitable container for disposal. Contact competent authorities after a spill. Absorb and/or contain spill with inert material. Do not take up in combustible material such as: saw dust or cellulosic material. Use only non- sparking tools.

#### 6.4. Reference to Other Sections

See Section 8 for exposure controls and personal protection and Section 13 for disposal considerations.

### **SECTION 7: Handling And Storage**

### 7.1. Precautions for Safe Handling

Additional Hazards When Processed Precautions for Safe Handling	<ul> <li>Handle empty containers with care because residual vapours are flammable.</li> <li>Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Take precautionary measures against static discharge.</li> <li>Use only non-sparking tools. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe vapours, mist, spray. Handle empty containers with care because they may still present a hazard. Do not get in eyes, on skin, or on clothing.</li> </ul>
---	---

Safety Data Sheet

According to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Hygiene Measures	Handle in accordance with good industrial hygiene and safety procedures.
7.2. Conditions for Safe Storag	e, Including Any Incompatibilities
Technical Measures	Comply with applicable regulations. Take action to prevent static discharges. Ground and bond container and receiving equipment. Use explosion-proof electrical, ventilating, and lighting equipment.
Storage Conditions	Store in a dry, cool place. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials. Store locked up/in a secure area. Store in a well-

Incompatible Materials

Strong acids, strong bases, strong oxidizers.

ventilated place. Keep container tightly closed. Keep in

#### 7.3. Specific End Use(S)

As a marking ink for silicone rubber parts and other components where the coating must maintain long term stability. For professional use only.

fireproof place.

### **SECTION 8: Exposure Controls/Personal Protection**

#### 8.1. Control Parameters

Tin organic compound	ds	-
Austria	MAK (mg/m³)	0,1 mg/m³ (except tri-n-Butyltin compounds-inhalable fraction)
Austria	MAK Short time value (mg/m³)	0,2 mg/m³ (except Tri-n-butyltin compounds-inhalable fraction)
Austria	OEL chemical category (AT)	Skin notation except Tri-n-butyltin compounds
Belgium	Limit value (mg/m³)	0,1 mg/m³
Belgium	Short time value (mg/m³)	0,2 mg/m³
Belgium	OEL chemical category (BE)	Skin
Bulgaria	OEL TWA (mg/m³)	0,1 mg/m³
Croatia	GVI (granična vrijednost izloženosti) (mg/m³)	0,1 mg/m³ (except Cyhexatin)
Croatia	KGVI (kratkotrajna granična vrijednost izloženosti) (mg/m³)	0,2 mg/m³ (except Cyhexatin)
Czech Republic	Expoziční limity (PEL) (mg/m³)	0,1 mg/m³
Czech Republic	OEL chemical category (CZ)	Potential for cutaneous absorption
Denmark	Grænsevædi (8 timer) (mg/m³)	0,1 mg/m³ (except Tri-n-butyltin compounds)
Estonia	OEL TWA (mg/m³)	0,1 mg/m³
Estonia	OEL STEL (mg/m³)	0,2 mg/m <sup>3</sup>
Estonia	OEL chemical category (ET)	Skin notation
Finland	HTP-arvo (8h) (mg/m³)	0,1 mg/m³
Finland	HTP-arvo (15 min)	0,3 mg/m³
Finland	OEL chemical category (FI)	Potential for cutaneous absorption
France	VLE (mg/m³)	0,2 mg/m³
France	VME (mg/m³)	0,1 mg/m³
Greece	OEL TWA (mg/m³)	0,1 mg/m³

	REACH) with its amendment Regulation (EU) 2015/830	
Greece	OEL STEL (mg/m³)	0,2 mg/m <sup>3</sup>
Greece	OEL chemical category (GR)	skin - potential for cutaneous absorption
Hungary	AK-érték	0,1 mg/m³
Hungary	CK-érték	0,4 mg/m <sup>3</sup>
Hungary	OEL chemical category (HU)	Potential for cutaneous absorption
Ireland	OEL (8 hours ref) (mg/m <sup>3</sup> )	0,1 mg/m <sup>3</sup>
Ireland	OEL (15 min ref) (mg/m3)	0,2 mg/m <sup>3</sup>
Lithuania	IPRV (mg/m <sup>3</sup> )	0,1 mg/m <sup>3</sup>
Lithuania	TPRV (mg/m <sup>3</sup> )	0,2 mg/m <sup>3</sup>
Lithuania	OEL chemical category (LT)	Skin notation
Norway	Grenseverdier (AN) (mg/m <sup>3</sup> )	0,1 mg/m <sup>3</sup>
Norway	Grenseverdier (Korttidsverdi)	
,	(mg/m3)	0,3 mg/m³ (value calculated)
Norway	OEL chemical category (NO)	Skin notation
Portugal	OEL TWA (mg/m³)	0,1 mg/m³
Portugal	OEL STEL (mg/m³)	0,2 mg/m <sup>3</sup>
Portugal	OEL chemical category (PT)	A4 - Not Classifiable as a Human Carcinogen,skin - potential for cutaneous exposure
Romania	OEL TWA (mg/m³)	0,05 mg/m³
Romania	OEL STEL (mg/m³)	0,15 mg/m <sup>3</sup>
Slovakia	NPHV (priemerná) (mg/m³)	0,1 mg/m³
Slovakia	NPHV (Hraničná) (mg/m³)	0,2 mg/m <sup>3</sup>
Slovakia	OEL chemical category (SK)	Potential for cutaneous absorption
Spain	VLA-ED (mg/m³)	0,1 mg/m³
Spain	VLA-EC (mg/m³)	0,2 mg/m³
Spain	OEL chemical category (ES)	skin - potential for cutaneous absorption
Sweden	nivågränsvärde (NVG) (mg/m³)	0,1 mg/m³ (total dust)
Sweden	kortidsvärde (KTV) (mg/m³)	0,2 mg/m³ (total dust)
Sweden	OEL chemical category (SE)	Skin notation
Switzerland	KZGW (mg/m³)	0,2 mg/m³ (inhalable dust)
Switzerland	MAK (mg/m³)	0,1 mg/m³ (inhalable dust)
Switzerland	OEL chemical category (CH)	Skin notation
United Kingdom	WEL TWA (mg/m³)	0,1 mg/m³ (except Cyhexatin)
United Kingdom	WEL STEL (mg/m³)	0,2 mg/m³ (except Cyhexatin)
United Kingdom	WEL chemical category	Potential for cutaneous absorption except Cyhexatin
Chromium oxide (Cr2C	03) (1308-38-9)	
Estonia	OEL TWA (mg/m <sup>3</sup> )	0,02 mg/m <sup>3</sup>
Estonia	OEL STEL (mg/m <sup>3</sup> )	0,06 mg/m <sup>3</sup>
Estonia	OEL chemical category (ET)	Carcinogenic substance, Sensitizer
Latvia	OEL TWA (mg/m <sup>3</sup> )	1 mg/m <sup>3</sup>
26/08/2020	EN (English)	7/18

	ylbenzene and xylene No.) 01-2119539452-40-0053	
EU	IOELV TWA (mg/m <sup>3</sup> )	221 mg/m <sup>3</sup> (pure)
EU	IOELV TWA (ppm)	50 ppm (pure)
EU	IOELV STEL (mg/m <sup>3</sup> )	442 mg/m <sup>3</sup> (pure)
EU	IOELV STEL (ppm)	100 ppm (pure)
EU	Notes	Possibility of significant uptake through the skin (pure)
Austria	MAK (mg/m³)	221 mg/m³ (all isomers)
Austria	MAK (ppm)	50 ppm (all isomers)
Austria	MAK Short time value (mg/m³)	442 mg/m <sup>3</sup>
Austria	MAK Short time value (ppm)	100 ppm
Belgium	Limit value (mg/m³)	221 mg/m³
Belgium	Limit value (ppm)	50 ppm
Belgium	Short time value (mg/m³)	442 mg/m <sup>3</sup>
Belgium	Short time value (ppm)	100 ppm
Belgium	OEL chemical category (BE)	Skin, Skin notation pure
Bulgaria	OEL TWA (mg/m³)	221 mg/m³ (pure)
Bulgaria	OEL TWA (ppm)	50 ppm (pure)
Bulgaria	OEL STEL (mg/m³)	442 mg/m³ (pure)
Bulgaria	OEL STEL (ppm)	100 ppm (pure)
Croatia	GVI (granična vrijednost izloženosti) (mg/m³)	221 mg/m³
Croatia	GVI (granična vrijednost izloženosti) (ppm)	50 ppm
Croatia	KGVI (kratkotrajna granična vrijednost izloženosti) (mg/m³)	442 mg/m <sup>3</sup>
Croatia	KGVI (kratkotrajna granična vrijednost izloženosti) (ppm)	100 ppm
Croatia	OEL chemical category (HR)	Skin notation
Croatia	Croatia - BLV	1,5 mg/l Parameter: Xylene - Medium: blood - Sampling time: at the end of the work shift (alcohol before exposure to Xylene raises occurrence) 1,5 g/g creatinine Parameter: Methylhippuric acid - Medium: urine - Sampling time: at the end of the work shift (calculated on the average Creatinine value of 1.2 g/L urine)
Cyprus	OEL TWA (mg/m³)	221 mg/m <sup>3</sup>
Cyprus	OEL TWA (ppm)	50 ppm
Cyprus	OEL STEL (mg/m³)	442 mg/m <sup>3</sup>
Cyprus	OEL STEL (ppm)	100 ppm
Cyprus	OEL chemical category (CY)	Skin-potential for cutaneous absorption

Czech Republic	Expoziční limity (PEL) (mg/m <sup>3</sup> )	200 mg/m <sup>3</sup>
Czech Republic	OEL chemical category (CZ)	Potential for cutaneous absorption
Czech Republic	Czech Republic - BLV	820 µmol/mmol Creatinine Parameter: Methylhippuric acid - Medium: urine - Sampling time: end of shift 1400 mg/g creatinine Parameter: Methylhippuric acid - Medium: urine - Sampling time: end of shift
Denmark	Grænsevædi (8 timer) (mg/m³)	109 mg/m³ (Xylene, all isomers)
Denmark	Grænsevædi (8 timer) (ppm)	25 ppm (Xylene, all isomers)
Estonia	OEL TWA (mg/m³)	200 mg/m <sup>3</sup>
Estonia	OEL TWA (ppm)	50 ppm
Estonia	OEL STEL (mg/m <sup>3</sup> )	450 mg/m <sup>3</sup>
Estonia	OEL STEL (ppm)	100 ppm
Estonia	OEL chemical category (ET)	Skin notation
Finland	HTP-arvo (8h) (mg/m <sup>3</sup> )	220 mg/m <sup>3</sup>
Finland	HTP-arvo (8h) (ppm)	50 ppm
Finland	HTP-arvo (15 min)	440 mg/m <sup>3</sup>
Finland	HTP-arvo (15 min) (ppm)	100 ppm
Finland	OEL chemical category (FI)	Potential for cutaneous absorption
Finland	Finland - BLV	Parameter: Methylhippuric acid - Medium: urine - Sampling time: after the shift
France	VLE (mg/m³)	442 mg/m³ (restrictive limit)
France	VLE (ppm)	100 ppm (restrictive limit)
France	VME (mg/m³)	221 mg/m³ (restrictive limit)
France	VME (ppm)	50 ppm (restrictive limit)
France	OEL chemical category (FR)	Risk of cutaneous absorption
France	France - BLV	1500 mg/g creatinine Parameter: Methylhippuric acid - Medium: urine - Sampling time: end of shift
Germany	Occupational exposure limit value (mg/m³)	440 mg/m³ (all isomers)
Germany	Occupational exposure limit value (ppm)	100 ppm (all isomers)
Germany	TRGS 903 Biological limit value	2000 mg/l Parameter: Methylhippuric(tolur-)acid (all isomers) - Medium: urine - Sampling time: end of shift (all isomers)
Germany	Chemical category	Skin notation all isomers
Gibraltar	Eight hours mg/m3	221 mg/m <sup>3</sup> (pure)
Gibraltar	Eight hours ppm	50 ppm (pure)
Gibraltar	Short-term mg/m3	442 mg/m <sup>3</sup> (pure)
	-	
Gibraltar	Short-term ppm	100 ppm (pure)

Greece	OEL TWA (mg/m <sup>3</sup> )	435 mg/m <sup>3</sup>
Greece	OEL TWA (ppm)	100 ppm
Greece	OEL STEL (mg/m <sup>3</sup> ) 650 mg/m <sup>3</sup>	
Greece	OEL STEL (ppm) 150 ppm	
Greece	OEL chemical category (GR)	skin - potential for cutaneous
		absorption
Hungary	AK-érték	221 mg/m <sup>3</sup>
Hungary	CK-érték	442 mg/m <sup>3</sup>
Hungary	OEL chemical category (HU)	Potential for cutaneous absorption
Ireland	OEL (8 hours ref) (mg/m <sup>3</sup> )	221 mg/m <sup>3</sup>
Ireland	OEL (8 hours ref) (ppm)	50 ppm
Ireland	OEL (15 min ref) (mg/m3)	442 mg/m <sup>3</sup>
Ireland	OEL (15 min ref) (ppm)	100 ppm
Ireland	OEL chemical category (IE)	Potential for cutaneous absorption
Italy	OEL TWA (mg/m <sup>3</sup> )	221 mg/m <sup>3</sup> (pure)
Italy	OEL TWA (ppm)	50 ppm (pure)
Italy	OEL STEL (mg/m³)	442 mg/m <sup>3</sup> (pure)
Italy	OEL STEL (ppm)	100 ppm (pure)
Italy	OEL chemical category (IT)	skin - potential for cutaneous
,		absorption pure
Latvia	OEL TWA (mg/m³)	221 mg/m³
Latvia	OEL TWA (ppm)	50 ppm
Latvia	OEL chemical category (LV)	skin - potential for cutaneous
		exposure
Lithuania	IPRV (mg/m³)	221 mg/m <sup>3</sup> (mixed isomers, pure)
Lithuania	IPRV (ppm)	50 ppm (mixed isomers, pure)
Lithuania	TPRV (mg/m³)	442 mg/m <sup>3</sup> (mixed isomers, pure)
Lithuania	TPRV (ppm)	100 ppm (mixed isomers, pure)
Lithuania	OEL chemical category (LT)	Skin notation
Luxembourg	OEL TWA (mg/m³)	221 mg/m <sup>3</sup>
Luxembourg	OEL TWA (ppm)	50 ppm
Luxembourg	OEL STEL (mg/m³)	442 mg/m <sup>3</sup>
Luxembourg	OEL STEL (ppm)	100 ppm
Luxembourg	OEL chemical category (LU)	Possibility of significant uptake
		through the skin
Malta	OEL TWA (mg/m³)	221 mg/m <sup>3</sup> (pure)
Malta	OEL TWA (ppm)	50 ppm (pure)
Malta	OEL STEL (mg/m³)	442 mg/m <sup>3</sup> (pure)
Malta	OEL STEL (ppm)	100 ppm (pure)
Malta	OEL chemical category (MT)	Possibility of significant uptake
		through the skin pure
Netherlands	Grenswaarde TGG 8H (mg/m³)	210 mg/m <sup>3</sup>
Netherlands	Grenswaarde TGG 15MIN (mg/m³)	442 mg/m³

Norway	Grenseverdier (AN) (mg/m <sup>3</sup> )	108 mg/m <sup>3</sup>	
Norway	Grenseverdier (AN) (ppm)	25 ppm	
Norway	Grenseverdier (Korttidsverdi) (mg/m3)	135 mg/m³ (value calculated)	
Norway	Grenseverdier (Korttidsverdi) (ppm)	37,5 ppm (value calculated)	
Norway	OEL chemical category (NO)	Skin notation	
Poland	NDS (mg/m <sup>3</sup> )	100 mg/m <sup>3</sup> (mixture of isomers)	
Poland	NDSCh (mg/m <sup>3</sup> )	200 mg/m <sup>3</sup> (mixture of isomers)	
Portugal	OEL TWA (mg/m <sup>3</sup> )	221 mg/m <sup>3</sup> (indicative limit value)	
Portugal	OEL TWA (ppm)	50 ppm (indicative limit value)	
Portugal	OEL STEL (mg/m <sup>3</sup> )	442 mg/m <sup>3</sup> (indicative limit value)	
Portugal	OEL STEL (ppm)	100 ppm (indicative limit value)	
Portugal	OEL chemical category (PT)	A4 - Not Classifiable as a Human Carcinogen	
Romania	OEL TWA (mg/m³)	221 mg/m <sup>3</sup> (pure)	
Romania	OEL TWA (ppm)	50 ppm (pure)	
Romania	OEL STEL (mg/m³)	442 mg/m³ (pure)	
Romania	OEL STEL (ppm)	100 ppm (pure)	
Romania	OEL chemical category (RO)	Skin notation pure	
Romania	Romania - BLV	3 g/l Parameter: Methylhippuric acid - Medium: urine - Sampling time: end of shift	
Slovakia	NPHV (priemerná) (mg/m³)	221 mg/m³	
Slovakia	NPHV (priemerná) (ppm)	50 ppm	
Slovakia	NPHV (Hraničná) (mg/m³)	442 mg/m <sup>3</sup>	
Slovakia	OEL chemical category (SK)	Potential for cutaneous absorption	
Slovakia	Slovakia - BLV	1,5 mg/l Parameter: Xylene - Medium: blood - Sampling time: end of exposure or work shift (all isomers) 2000 mg/l Parameter: Methylhippuric acid - Medium: urine - Sampling time: end of exposure or work shift	
Slovenia	OEL TWA (mg/m³)	221 mg/m³	
Slovenia	OEL TWA (ppm)	50 ppm	
Slovenia	OEL STEL (mg/m³)	442 mg/m <sup>3</sup>	
Slovenia	OEL STEL (ppm)	100 ppm	
Slovenia	OEL chemical category (SI)	Potential for cutaneous absorption	
Spain	VLA-ED (mg/m³)	221 mg/m³ (indicative limit value)	
Spain	VLA-ED (ppm)	50 ppm (indicative limit value)	
Spain	VLA-EC (mg/m³)	442 mg/m <sup>3</sup>	
Spain	VLA-EC (ppm)	100 ppm	
Spain	OEL chemical category (ES)	skin - potential for cutaneous absorption	

Safety Data Sheet

According to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Spain	Spain - BLV	1 g/g creatinine Parameter: Methylhippuric acids - Medium: urine - Sampling time: end of shift
Sweden	nivågränsvärde (NVG) (mg/m³)	221 mg/m³ (Xylene)
Sweden	nivågränsvärde (NVG) (ppm)	50 ppm (Xylene)
Sweden	kortidsvärde (KTV) (mg/m³)	442 mg/m <sup>3</sup> (Xylene)
Sweden	kortidsvärde (KTV) (ppm)	100 ppm (Xylene)
Sweden	OEL chemical category (SE)	Skin notation
Switzerland	KZGW (mg/m³)	870 mg/m <sup>3</sup>
Switzerland	KZGW (ppm)	200 ppm
Switzerland	MAK (mg/m³)	435 mg/m <sup>3</sup>
Switzerland	MAK (ppm)	100 ppm
Switzerland	OEL chemical category (CH)	Skin notation
Switzerland	Switzerland - BLV	2 g/l Parameter: Methylhippuric acid - Medium: urine - Sampling time: end of shift
United Kingdom	WEL TWA (mg/m³)	220 mg/m <sup>3</sup>
United Kingdom	WEL TWA (ppm)	50 ppm
United Kingdom	WEL STEL (mg/m³)	441 mg/m <sup>3</sup>
United Kingdom	WEL STEL (ppm)	100 ppm
United Kingdom	WEL chemical category	Potential for cutaneous absorption

#### 8.2. Exposure Controls

Appropriate Engineering Controls

Personal Protective Equipment

Materials for Protective Clothing

Hand Protection Eye Protection Skin and Body Protection Respiratory Protection

Other Information

Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure adequate ventilation, especially in confined areas. Ensure all national/local regulations are observed. Gas detectors should be used when flammable gases or vapors may be released. Proper grounding procedures to avoid static electricity should be followed. Use explosion-proof equipment. Gloves. Protective clothing. Protective goggles. Insufficient ventilation: wear respiratory protection.



Chemically resistant materials and fabrics. Wear fire/flame resistant/retardant clothing. Wear protective gloves. Chemical safety goggles. Wear suitable protective clothing. If exposure limits are exceeded or irritation is experienced, approved respiratory protection should be worn. In case of inadequate ventilation, oxygen deficient atmosphere, or where exposure levels are not known wear approved respiratory protection. When using, do not eat, drink or smoke.

### **SECTION 9: Physical and Chemical Hazards**

### 9.1. Information on Basic Physical and Chemical Properties

**Physical State** Liquid Colour Green Odour Solvent Odour Threshold No data available рΗ No data available **Evaporation Rate** No data available Melting Point No data available Freezing Point No data available **Boiling Point** 140 °C (284 °F) Flash Point 27 °C (81 °F) Auto-Ignition Temperature No data available **Decomposition Temperature** No data available Flammability (Solid, Gas) Not applicable Vapour Pressure No data available Relative Vapour Density At 20 °C No data available Specific Gravity > 1 **Relative Density** No data available Solubility No data available Partition Coefficient n-Octanol/Water No data available Viscosity, Kinematic No data available Viscosity, Dynamic No data available **Explosive Properties** No data available **Oxidising Properties** No data available **Explosive Limits** No data available 9.2. Other Information

#### VOC content

10 - 30 %

### **SECTION 10: Stability and Reactivity**

#### 10.1. Reactivity

Reacts violently with strong oxidisers. Increased risk of fire or explosion.

#### 10.2. Chemical Stability

Flammable liquid and vapour. May form flammable or explosive vapour-air mixture.

#### 10.3. Possibility Of Hazardous Reactions

Hazardous polymerization will not occur.

#### 10.4. Conditions To Avoid

Direct sunlight, extremely high or low temperatures, heat, hot surfaces, sparks, open flames, incompatible materials, and other ignition sources.

#### 10.5. Incompatible Materials

Strong acids, strong bases, strong oxidizers.

#### 10.6. Hazardous Decomposition Products

None expected under normal conditions of use.

Safety Data Sheet

According to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### **SECTION 11: Toxicological Information**

### 11.1. Information On Toxicological Effects

Acute Toxicity

Not classified (Based on available data, the classification criteria are not met)

R-1008-6		
ATE CLP (oral)	2000 mg/kg bodyweight	
Dibutyltin dilaurate (77-58-7)		
LD50 Oral	175 mg/kg	
LD50 Dermal Rat	> 2 g/kg	
2-Butanone, O,O',O''-(methylsilylic	lyne)trioxime (22984-54-9)	
LD50 Oral Rat	2463 mg/kg	
LD50 Dermal Rat	> 2000 mg/kg	
Chromium oxide (Cr2O3) (1308-38	3-9)	
LD50 Oral Rat	> 5000 mg/kg	
Reaction mass of ethylbenzene a (REACH Registration No.) 01-2119.		
LD50 Oral Rat	3523 mg/kg	
LC50 Inhalation Rat	6700 ppm/4h	
ATE CLP (oral)	3523 mg/kg bodyweight	
ATE CLP (dermal)	1100 mg/kg bodyweight	
ATE CLP (gases)	6700 ppmv/4h	
ATE CLP (vapours)	11 mg/l/4h	
Skin Corrosion/Irritation Eye Damage/Irritation Respiratory or Skin Sensitization Germ Cell Mutagenicity	Causes skin irritation. Causes serious eye irritation. May cause an allergic skin reaction. Not classified (Based on available data, the classification criteria are not met)	
Carcinogenicity	Not classified (Based on available data, the classification criteria are not met)	
Reproductive Toxicity	Not classified (Based on available data, the classification criteria are not met)	
Specific Target Organ Toxicity (Single Exposure)	May cause respiratory irritation.	
Specific Target Organ Toxicity (Re Exposure)	prolonged or repeated exposure (oral).	
Aspiration Hazard	May be fatal if swallowed and enters airways.	

## **SECTION 12: Ecological Information**

### 12.1. Toxicity

Ecology - General	Toxic to aquatic life.	
Dibutyltin dilaurate (77-58-7)		
EC50 Daphnia 1	0,463 mg/l (Daphnia magna)	
2-Butanone, O,O',O''-(methylsilylic	lyne)trioxime (22984-54-9)	
EC50 Daphnia 1	120 mg/l (Exposure time: 48h - Species: Daphnia magna)	
26/08/2020	EN (English)	14/18

#### Safety Data Sheet

According to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Chromium oxide (Cr2O3) (1308-38-9)		
LC50 Fish 1       > 10000 mg/l (Exposure time: 96 h - Species: Danio rerio [static])		
NOEC Chronic Fish1000 mg/l (Species: Brachydanio rerio - Duration: 30 d)		

#### 12.2. Persistence and Degradability

#### R-1008-6

Persistence and Degradability Not established.

#### 12.3. Bioaccumulative Potential

R-1008-6	
Bioaccumulative potential	Not established.
DibutyItin dilaurate (77-58-7)	
Log Pow	4,44

#### 12.4. Mobility in Soil

No additional information available

#### 12.5. Results of PBT and vPvB assessment

No additional information available

#### 12.6. Other Adverse Effects

Other Information

Avoid release to the environment.

### **SECTION 13: Disposal Considerations**

#### 13.1. Waste Treatment Methods

Product/Packaging Disposal	Dispose of contents/container in accordance with local,
Recommendations	regional, national, and international regulations.
Additional Information	Handle empty containers with care because residual vapours are flammable.
Ecology - Waste Materials	Avoid release to the environment. This material is hazardous to the aquatic environment. Keep out of sewers and waterways.

### **SECTION 14: Transport Information**

The shipping description(s) stated herein were prepared in accordance with certain assumptions at the time the SDS was authored, and can vary based on a number of variables that may or may not have been known at the time the SDS was issued.

In accordance with ADR / RID / IMDG / IATA / ADN

ADR	IMDG	IATA	ADN	RID
14.1. UN Nun				
1307	1307	1307	1307	1307
14.2. UN Prop	per Shipping Name	9		
XYLENES	XYLENES	XYLENES	XYLENES	XYLENES
Solution	SOLUTION	SOLUTION	SOLUTION	SOLUTION
14.3. Transpo	ort Hazard Class(Es	<b>;</b> ]	÷	·
3	3	3	3	3
14.4. Packing	g Group	· ·	· ·	

#### Safety Data Sheet

According to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

ADR	IMDG	IATA	ADN	RID
14.5. Environme	ntal Hazards			
Dangerous for the environment : No	Dangerous for the environment : No Marine pollutant : No	Dangerous for the environment : No	Dangerous for the environment : No	Dangerous for the environment : No

#### 14.6. Special Precautions For User

No additional information available

**14.7. Transport in Bulk According to Annex II of MARPOL and The IBC Code** Not applicable

### **SECTION 15: Regulatory Information**

# 15.1. Safety, Health and Environmental Regulations/Legislation Specific for the Substance or Mixture

#### 15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions Contains no substance on the REACH candidate list Contains no REACH Annex XIV substances

#### 15.1.2. National Regulations

No additional information available

#### 15.2. Chemical Safety Assessment

No chemical safety assessment has been carried out

### **SECTION 16: Other Information**

#### Indication of Changes

Section	Section Header	Change	Date Changed
1	Identification of the substance/mixture and of the company/undertaking	Modified	26/08/2020
2	Hazards identification	Modified	26/08/2020
3	Composition/information on ingredients	Modified	26/08/2020
4	First aid measures	Modified	26/08/2020
8	Exposure controls/personal protection	Modified	26/08/2020
9	Physical and chemical properties	Modified	26/08/2020
10	Stability and reactivity	Modified	26/08/2020
11	Toxicological information	Modified	26/08/2020

Date of Preparation or Latest 26/08/2020 Revision Data Sources Information

Information and data obtained and used in the authoring of this safety data sheet could come from database subscriptions, official government regulatory body websites, product/ingredient manufacturer or supplier specific information, and/or resources that include substance specific data and classifications according to GHS or their subsequent adoption of GHS.

Safety Data Sheet According to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Other Information

According to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Full Text of H- and EUH-statements:

Il Text of H- and EUH-statements:		
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4	
Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4	
Acute Tox. 4 (Inhalation:vapour)	Acute toxicity (inhalation:vapour) Category 4	
Aquatic Acute 1	Hazardous to the aquatic environment — Acute	
	Hazard, Category 1	
Aquatic Chronic 1	Hazardous to the aquatic environment — Chronic	
	Hazard, Category 1	
Asp. Tox. 1	Aspiration hazard, Category 1	
Eye Dam. 1	Serious eye damage/eye irritation, Category 1	
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2	
Flam. Liq. 3	Flammable liquids, Category 3	
Muta. 2	Germ cell mutagenicity, Category 2	
Repr. 1B	Reproductive toxicity, Category 1B	
Skin Corr. 1C	Skin corrosion/irritation, Category 1C	
Skin Irrit. 2	Skin corrosion/irritation, Category 2	
Skin Sens. 1	Skin sensitisation, Category 1	
Skin Sens. 1B	Skin sensitisation, category 1B	
STOT RE 1	Specific target organ toxicity — Repeated exposure,	
	Category 1	
STOT RE 2	Specific target organ toxicity — Repeated exposure,	
	Category 2	
STOT SE 1	Specific target organ toxicity — Single exposure,	
	Category 1	
STOT SE 3	Specific target organ toxicity — Single exposure,	
	Category 3, Respiratory tract irritation	
H226	Flammable liquid and vapour.	
H304	May be fatal if swallowed and enters airways.	
H312	Harmful in contact with skin.	
H314	Causes severe skin burns and eye damage.	
H315	Causes skin irritation.	
H317	May cause an allergic skin reaction.	
H318	Causes serious eye damage.	
H319	Causes serious eye irritation.	
H332	Harmful if inhaled.	
H335	May cause respiratory irritation.	
H341	Suspected of causing genetic defects.	
H360	May damage fertility or the unborn child.	
H370	Causes damage to organs.	
H372	Causes damage to organs through prolonged or	
	repeated exposure.	
H373	May cause damage to organs through prolonged or	
	repeated exposure.	
H400	Very toxic to aquatic life.	
H410	Very toxic to aquatic life with long lasting effects.	

Safety Data Sheet

According to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

#### Abbreviations and Acronyms

ACGIH – American Conference of Governmental Industrial Hyaienists ADN – European Agreement Concerning the International Carriage of Dangerous Goods by Inland Waterways ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road ATE - Acute Toxicity Estimate BCF - Bioconcentration Factor BEI - Biological Exposure Indices (BEI) BOD - Biochemical Oxygen Demand CAS No. - Chemical Abstracts Service Number CLP - Classification, Labeling and Packaging Regulation (EC) No 1272/2008 COD – Chemical Oxygen Demand EC – European Community EC50 - Median Effective Concentration EEC - European Economic Community EINECS – European Inventory of Existing Commercial Chemical Substances EmS-No. (Fire) - IMDG Emergency Schedule Fire EmS-No. (Spillage) - IMDG Emergency Schedule Spillage FU - European Union ErC50 - EC50 in Terms of Reduction Growth Rate GHS - Globally Harmonized System of Classification and Labeling of Chemicals IARC - International Agency for Research on Cancer IATA - International Air Transport Association IBC Code - International Bulk Chemical Code IMDG - International Maritime Dangerous Goods IPRV - Ilgalaikio Poveikio Ribinis Dydis IOELV - Indicative Occupational Exposure Limit Value LC50 - Median Lethal Concentration LD50 - Median Lethal Dose LOAEL - Lowest Observed Adverse Effect Level LOEC - Lowest-Observed-Effect Concentration Log Koc - Soil Organic Carbon-water Partitioning Coefficient Log Kow - Octanol/water Partition Coefficient Log Pow - Ratio of the equilibrium concentration (C) of a dissolved substance in a two-phase system consisting of two largely immiscible solvents, in this case octanol and water MAK - Maximum Workplace Concentration/Maximum Permissible Concentration

MAR – Maximum Workplace Concentration/Maximum Permissible Concentration MARPOL - International Convention for the Prevention of Pollution NDS - Naiwyzsze Dopuszczalne Stezenie NDSCh - Najwyzsze Dopuszczalne Stezenie Chwilowe NDSP - Naiwyzsze Dopuszczalne Stezenie Pulapowe NOAEL - No-Observed Adverse Effect Level NOEC - No-Observed Effect Concentration NRD - Nevirsytings Ribinis Dydis NTP – National Toxicology Program OEL - Occupational Exposure Limits PBT - Persistent, Bioaccumulative and Toxic PEL - Permissible Exposure Limit pH – Potential Hydrogen . REACH – Registration, Evaluation, Authorisation, and Restriction of Chemicals RID - Regulations Concerning the International Carriage of Dangerous Goods by Rail SADT - Self Accelerating Decomposition Temperature SDS - Safety Data Sheet STEL - Short Term Exposure Limit STOT - Specific Target Organ Toxicity TA-Luft - Technische Anleitung zur Reinhaltung der Luft TEL TRK - Technical Guidance Concentrations ThOD – Theoretical Oxygen Demand TLM - Median Tolerance Limit TLV - Threshold Limit Value TPRD - Trumpalaikio Poveikio Ribinis Dydis TRGS 510 - Technische Regel für Gefahrstoffe 510 - Lagerung von Gefahrstoffen in ortsbeweglichen Behältern TRGS 552 – Technische Regeln für Gefahrstoffe - N-Nitrosamine TRGS 900 - Technische Regel für Gefahrstoffe 900 – Arbeitsplatzgrenzwerte TRGS 903 - Technische Regel für Gefahrstoffe 903 - Biologische Grenzwerte TSCA - Toxic Substances Control Act TWA - Time Weighted Average VOC – Volatile Organic Compounds VLA-EC - Valor Límite Ambiental Exposición de Corta Duración VLA-ED - Valor Límite Ambiental Exposición Diaria VLE – Valeur Limite D'exposition VME - Valeur Limite De Movenne Exposition vPvB - Very Persistent and Very Bioaccumulative WEL – Workplace Exposure Limit WGK - Wassergefährdungsklasse

Nusil EU GHS SDS

The information provided in this Safety Data Sheet (SDS) was prepared based on data believed to be accurate as of the date of this SDS. TO THE GREATEST EXTENT PERMITTED BY LAW, NUSIL TECHNOLOGY LLC AND ITS AFFILIATED COMPANIES ("NUSIL") EXPRESSLYDISCLAIMS ANY AND ALL REPRESENTATIONS AND WARRANTIES REGARDING THE INFORMATION CONTAINED HEREIN INCLUDING, WITHOUT LIMITATION, AS TO ACCURACY, COMPLETENESS, FITNESS FOR PURPOSE OR USE, MERCHANTABILITY, NON-INFRINGEMENT, PERFORMANCE, SAFETY, SUITABILITY AND STABILITY. This SDS is intended as a guide to the appropriate use, handling, storage and disposal of the product to which it relates by properly trained personnel, and is not intended to be comprehensive. Users of NuSil's products are advised to perform their own tests and to exercise their own judgment to determine the safety, suitability and appropriate use, handling, storage and disposal of each product and product combination for their own purposes and uses. TO THE GREATEST EXTENT PERMITTED BY LAW, NUSIL DISCLAIMS LIABILITY FOR, AND BY USING NUSIL'S PRODUCTS PURCHASER AGREES THAT UNDER NO CIRCUMSTANCES SHALL NUSIL BE LIABLE FOR. SPECIAL, INDIRECT, INCIDENTAL, PUNITIVE OR CONSEQUENTIAL DAMAGES OF ANY TYPE OR KIND. INCLUDING WITHOUT LIMITATION, FOR LOSS OF PROFITS, REPUTATIONAL DAMAGE, PRODUCT RECALL OR BUSINESS INTERRUPTION.