MED-1131





Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Revision Date: 02/27/2023 Date of Issue: 02/17/2014

Version: 3.0

SECTION 1: Identification

1.1. Product Identifier

Product Form Product Name Synonyms Mixture MED-1131 Silicone Adhesive

1.2. Relevant Identified Uses of the Substance or Mixture and Uses Advised Against

Use of the Substance/Mixture For professional use only.

1.3. Details of the Supplier of the Safety Data Sheet

NuSil Technology LLC 1050 Cindy Lane Carpinteria, California 93013 USA (805) 684-8780 productstewardship@avantorsciencesgcc.com www.nusil.com

1.4. Emergency Telephone Number

Emergency 800-424-9300 CHEMTREC (in US); +1 703-527-3887 CHEMTREC (International and Maritime)

SECTION 2: Hazards Identification

2.1. Classification of the Substance or Mixture

GHS-US Classification

Eye Irrit. 2 H319 Skin Sens. 1 H317 Repr. 1B H360 STOT RE 2 H373 Full text of hazard classes and H-statements: see section 16

2.2. Label Elements

GHS-US Labeling

Hazard Pictograms (GHS-US)



Signal Word (GHS-US) Hazard Statements (GHS-US)

Danger H317 - May cause an allergic skin reaction H319 - Causes serious eye irritation H360 - May damage fertility or the unborn child H373 - May cause damage to organs (blood) through prolonged or repeated exposure (oral) Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Precautionary Statements (GHS-P201 - Obtain special instructions before use. US) P202 - Do not handle until all safety precautions have been read and understood. P260 - Do not breathe vapors, mist, spray. P264 - Wash hands, forearms, exposed areas thoroughly after handlina. P272 - Contaminated work clothing must not be allowed out of the workplace. P280 - Wear eye protection, protective gloves, protective clothina. P302+P352 - If on skin: Wash with plenty of soap and water. P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P308+P313 - If exposed or concerned: Get medical advice/attention. P314 - Get medical advice/attention if you feel unwell. P321 - Specific treatment (see Section 4 on this SDS). P333+P313 - If skin irritation or rash occurs: Get medical advice/attention. P337+P313 - If eye irritation persists: Get medical advice/attention. P363 - Wash contaminated clothing before reuse. P405 - Store locked up. P501 - Dispose of contents/container in accordance with local, regional, national, and international regulations. 2.3. Other Hazards

Other Hazards Not Contributing to the Classification

Exposure may aggravate pre-existing eye, skin, or respiratory conditions.

2.4. Unknown Acute Toxicity (GHS-US)

No data available

SECTION 3: Composition/Information On Ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product Identifier	%	GHS-US Classification
Silanamine, 1,1,1-trimethyl-N- (trimethylsilyl)-, hydrolysis products with silica	(CAS-No.) 68909-20-6	10 - 30	Not classified
2-Butanone, O,O',O''- (methylsilylidyne)trioxime	(CAS-No.) 22984-54-9	5 - 15	Eye Irrit. 2A, H319 Skin Sens. 1B, H317 STOT RE 2, H373
N-[3-(Trimethoxysilyl)propyl]-1,2- ethanediamine	(CAS-No.) 1760-24-3	< 1	Acute Tox. 4 (Inhalation:dust,mist), H332 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Acute 2, H401
Dibutyltin dilaurate	(CAS-No.) 77-58-7	< 0.3	Skin Irrit. 2, H315
02/27/2023 EN (English US)			2/12

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Eye Dam. 1, H318 Skin Sens. 1, H317
Muta. 2, H341
Repr. 1B, H360
STOT SE 1, H370
STOT RE 1, H372
Aquatic Acute 1, H400
Aquatic Chronic 1, H410

Full text of H-phrases: see section 16

The specific chemical identity and/or exact percentage of composition have been withheld as a trade secret [29 CFR 1910.1200].

SECTION 4: First Aid Measures

4.1. Description of First-aid Measures

First-aid Measures General	Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid Measures After	When symptoms occur: go into open air and ventilate
Inhalation	suspected area. Obtain medical attention if breathing difficulty persists.
First-aid Measures After Skin	Remove contaminated clothing. Immediately drench affected
Contact	area with water for at least 15 minutes. Obtain medical attention if irritation/rash develops or persists.
First-aid Measures After Eye	Immediately rinse with water for at least 15 minutes. Remove
Contact	contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention.
First-aid Measures After	Do NOT induce vomiting. Rinse mouth. Obtain medical
Ingestion	attention.
4.2. Most Important Symptoms	and Effects Both Acute and Delayed
Symptoms/Injuries	Causes serious eye irritation. Skin sensitization. May damage fertility. May damage the unborn child. May cause damage to organs through prolonged or repeated exposure.
Symptoms/Injuries After Inhalation	Prolonged exposure may cause irritation.
Symptoms/Injuries After Skin Contact	May cause an allergic skin reaction.
Symptoms/Injuries After Eye Contact	Redness, pain, swelling, itching, burning, tearing, and blurred vision.
Symptoms/Injuries After Ingestion	Ingestion may cause adverse effects.
Chronic Symptoms	May damage fertility or the unborn child. May cause damage to organs (blood) through prolonged or repeated exposure (oral).

4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention. If medical advice is needed, have product container or label at hand.

SECTION 5: Fire-Fighting Measures

5.1. **Extinguishing Media**

Suitable Extinguishing Media Unsuitable Extinguishing Media	 : Use extinguishing media appropriate for surrounding fire. : Do not use a heavy water stream. Use of heavy stream of water may spread fire. Application of water stream to hot product may cause frothing and increase fire intensity.
5.2. Special Hazards Arising F	From the Substance or Mixture
Fire Hazard	Not considered flammable but may burn at high temperatures.
Explosion Hazard	Product is not explosive.
Reactivity	Hazardous reactions will not occur under normal conditions.
5.3. Advice for Firefighters	

Precautionary Measures Fire Exercise caution when fighting any chemical fire. **Firefighting Instructions** Use water spray or fog for cooling exposed containers. Do not allow run-off from fire fighting to enter drains or water sources.

Protection During Firefighting	Do not enter fire area without proper protective equipment,
	including respiratory protection.
Hazardous Combustion	Silicon oxides. Carbon oxides (CO, CO ₂). Nitrogen compounds.
Products	Formaldehyde. Oxides of tin.

SECTION 6: Accidental Release Measures

۲ ۱ Personal Precautions Protective Equipment And Emergency Procedures

	hecine Equipment And Emergency Hocedores
General Measures	Do not get in eyes, on skin, or on clothing. Do not breathe vapor, mist or spray.
6.1.1. For Non-Emergency Person	inei
Protective Equipment	Use appropriate personal protective equipment (PPE).
Emergency Procedures	Evacuate unnecessary personnel. Evacuate unnecessary personnel.
6.1.2. For emergency responders	
Protective Equipment	Equip cleanup crew with proper protection.
Emergency Procedures	Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit. Ventilate area.
6.2. Environmental Precaution	ns
Prevent entry to sewers and public	c waters. Notify authorities if liquid enters sewers or public waters.
6.3. Methods and Materials for	or Containment and Cleaning Up
For Containment	Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

Methods for Cleaning Up

Clean up spills immediately and dispose of waste safely. Contact competent authorities after a spill. Transfer spilled material to a suitable container for disposal.

6.4. **Reference to Other Sections**

See Section 8 for exposure controls and personal protection and Section 13 for disposal considerations.

SECTION 7: Handling And Storage

7.1. Precautions for Safe Handling

Additional Hazards When Processed	When heated, material emits irritating fumes. Any proposed use of this product in elevated-temperature processes should be thoroughly evaluated to assure that safe operating conditions are established and maintained.
Precautions for Safe Handling	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe vapors, mist, spray. Avoid contact with skin, eyes and clothing. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.
Hygiene Measures	Handle in accordance with good industrial hygiene and safety procedures.
7.2. Conditions for Safe Storage	e, Including Any Incompatibilities
Technical Measures	Comply with applicable regulations.
Storage Conditions	Keep container closed when not in use. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials. Store in a dry, cool place. Store locked up/in a secure area.
Incompatible Materials	Strong acids, strong bases, strong oxidizers.
7.3. Specific End Use(s) For professional use only.	

SECTION 8: Exposure Controls/Personal Protection

8.1. Control Parameters

For substances listed in section 3 that are not listed here, there are no established exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), or OSHA (PEL).

Silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, hydrolysis products with silica (68909-20-6)		
USA OSHA	OSHA PEL (TWA) (mg/m³)	6 mg/m ³
USA OSHA	OSHA PEL (TWA) (ppm)	20 mppcf (80 mg/m³/%SiO ₂)
Tin organic compounds		
USA ACGIH	ACGIH TWA (mg/m³)	0.1 mg/m ³
USA ACGIH	ACGIH STEL (mg/m³)	0.2 mg/m ³
USA ACGIH	ACGIH chemical category	Skin - potential significant contribution
		to overall exposure by the cutaneous
		route. Not Classifiable as a Human
		Carcinogen
USA OSHA	OSHA PEL (TWA) (mg/m³)	0.1 mg/m ³

8.2. Exposure Controls

Appropriate Engineering Controls Ensure adequate ventilation, especially in confined areas. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure all national/local regulations are observed. Personal Protective Equipment

Protective goggles. Gloves. Protective clothing. Insufficient ventilation: wear respiratory protection.



Materials For Protective Clothing Hand Protection Eye And Face Protection Skin And Body Protection Respiratory Protection Chemically resistant materials and fabrics.

Wear protective gloves. Chemical safety goggles. Wear suitable protective clothing. If exposure limits are exceeded or irritation is experienced, approved respiratory protection should be worn. In case of inadequate ventilation, oxygen deficient atmosphere, or where exposure levels are not known wear approved respiratory protection. When using, do not eat, drink or smoke.

Other Information

SECTION 9: Physical and Chemical Properties

9.1. Information on Basic Physical and Chemical Properties

Physical State	Liquid
Appearance	Translucent
Odor	Characteristic
Odor Threshold	No data available
рН	No data available
Evaporation Rate	No data available
Melting Point	No data available
Freezing Point	No data available
Boiling Point	No data available
Flash Point	> 135 ℃ (275 °F)
Auto-ignition Temperature	No data available
Decomposition Temperature	No data available
Flammability (solid, gas)	Not applicable
Vapor Pressure	No data available
Relative Vapor Density at 20 °C	No data available
Relative Density	> 1 (water = 1)
Specific Gravity	>]
Solubility	No data available
Partition Coefficient n-Octanol/Water	No data available
Viscosity	No data available
9.2. Other Information	
VOC Content	< 1%

SECTION 10: Stability and Reactivity

10.1. Reactivity

Hazardous reactions will not occur under normal conditions.

Safety Data Sheet According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

10.2. Chemical Stability

Stable under recommended handling and storage conditions (see section 7).

10.3. Possibility of Hazardous Reactions

Hazardous polymerization will not occur.

10.4. Conditions to Avoid

Direct sunlight, extremely high or low temperatures, and incompatible materials.

10.5. Incompatible Materials

Strong acids, strong bases, strong oxidizers.

10.6. Hazardous Decomposition Products

Will decompose above 150 °C (> 300 °F) releasing formaldehyde vapors. Formaldehyde is a potential carcinogen and can act as a potential skin and respiratory sensitizer. Formaldehyde can also cause respiratory and eye irritation.

SECTION 11: Toxicological Information

11.1. Information on Toxicological Effects

Acute Toxicity (Oral)	: Not classified
Acute Toxicity (Dermal)	: Not classified
Acute Toxicity (Inhalation)	: Not classified
2-Butanone, O,O',O''-(methylsilyli	dyne)trioxime (22984-54-9)
LD50 Oral Rat	2463 mg/kg
LD50 Dermal Rat	> 2000 mg/kg
N-[3-(Trimethoxysilyl)propyl]-1,2-e	thanediamine (1760-24-3)
LD50 Oral Rat	2295 mg/kg
LD50 Dermal Rabbit	> 2000 mg/kg
LC50 Inhalation Rat	> 1.49 mg/l/4h
ATE (Dust/Mist)	1.50 mg/l/4h
Dibutyltin dilaurate (77-58-7)	
LD50 Dermal Rat	> 2 g/kg
Skin Corrosion/Irritation	Not classified
Serious Eye Damage/Irritation	Causes serious eye irritation.
Respiratory or Skin Sensitization	May cause an allergic skin reaction.
Germ Cell Mutagenicity	Not classified
Carcinogenicity	Not classified
Reproductive Toxicity	: May damage fertility or the unborn child.
Specific Target Organ Toxicity (Si	
Specific Target Organ Toxicity (R	
Exposure)	prolonged or repeated exposure (oral).
Aspiration Hazard	Not classified
Symptoms/Injuries After	Prolonged exposure may cause irritation.
Inhalation	
Symptoms/Injuries After Skin	May cause an allergic skin reaction.
Contact	
Symptoms/Injuries After Eye	Redness, pain, swelling, itching, burning, tearing, and blurred
Contact	vision.
Symptoms/Injuries After	Ingestion may cause adverse effects.
Ingestion	

Chronic Symptoms May damage fertility or the unborn child. May cause damage to organs (blood) through prolonged or repeated exposure (oral).

SECTION 12: Ecological Information

12.1. Toxicity

Ecology - General	Not classified.		
2-Butanone, O,O',O''-(methylsilyli	2-Butanone, O,O',O''-(methylsilylidyne)trioxime (22984-54-9)		
EC50 Daphnia 1	120 mg/l (Exposure time: 48h - Species: Daphnia magna)		
N-[3-(Trimethoxysilyl)propyl]-1,2-ethanediamine (1760-24-3)			
LC50 Fish 1	597 mg/l (Species: Danio rerio)		
EC50 Daphnia 1	81 mg/l		
ErC50 (Algae)	8.8 mg/l (Exposure time: 72 h - Species: Pseudokirchneriella		
	subcapitata)		
NOEC Chronic Fish	344 mg/l		
NOEC Chronic Crustacea	35 mg/l		
NOEC Chronic Algae	3.1 mg/l (Pseudokirchnerella subcapitata Exposure time: 96h)		
Dibutyltin dilaurate (77-58-7)			
EC50 Daphnia 1	0.463 mg/l (Daphnia magna)		

12.2. Persistence and Degradability

MED-1131		
Persistence and Degradability	Not established.	
12.3. Bioaccumulative Potential		
MED-1131		
Bioaccumulative Potential	Not established.	

Log Pow

12.4. Mobility In Soil No additional information available

Dibutyltin dilaurate (77-58-7)

12.5. Other Adverse Effects

Other Information

Avoid release to the environment.

SECTION 13: Disposal Considerations

13.1. Waste Treatment Methods

Waste Disposal	Dispose of contents/container in accordance with local,
Recommendations	regional, national, and international regulations.
Additional Information	Container may remain hazardous when empty. Continue to observe all precautions.
Ecology - Waste Materials	Avoid release to the environment.

SECTION 14: Transport Information

The shipping description(s) stated herein were prepared in accordance with certain assumptions at the time the SDS was authored, and can vary based on a number of variables that may or may not have been known at the time the SDS was issued.

4 44

- 14.1. In Accordance with DOT Not regulated for transport
- **14.2.** In Accordance with IMDG Not regulated for transport
- 14.3. In Accordance with IATA Not regulated for transport

SECTION 15: Regulatory Information

15.1. US Federal Regulations

All components in this mixture are listed on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory, have been exempted, or are not disclosed due to CBI requirements or disclosure rules according to the relevant regulation.

MED-1131	
SARA Section	Health hazard - Specific target organ toxicity (single or repeated exposure)
311/312 Hazard	Health hazard - Respiratory or skin sensitization
Classes	Health hazard - Serious eye damage or eye irritation
	Health hazard - Reproductive toxicity

15.2. US State Regulations

2-Butanone, O,O',O''-(methylsilylidyne)trioxime (22984-54-9)		
U.S Texas - Effects Screening Levels - Long Term		
U.S Texas - Effects Screening Levels - Short Term		
N-[3-(TrimethoxysilyI)propyl]-1,2-ethanediamine (1760-24-3)		
U.S Texas - Effects Screening Levels - Long Term		
U.S Texas - Effects Screening Levels - Short Term		
Silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, hydrolysis products with silica (68909-20-6)		
U.S Texas - Effects Screening Levels - Long Term		
U.S Texas - Effects Screening Levels - Short Term		
Tin organic compounds (Not applicable)		

MED-1131

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

- U.S. Connecticut Hazardous Air Pollutants HLVs (30 min)
- U.S. Connecticut Hazardous Air Pollutants HLVs (8 hr)
- U.S. Idaho Non-Carcinogenic Toxic Air Pollutants Acceptable Ambient Concentrations
- U.S. Idaho Non-Carcinogenic Toxic Air Pollutants Emission Levels (ELs)
- U.S. Idaho Occupational Exposure Limits TWAs
- U.S. Michigan Occupational Exposure Limits Skin Designations
- U.S. Michigan Occupational Exposure Limits TWAs
- U.S. Minnesota Hazardous Substance List
- U.S. Minnesota Permissible Exposure Limits Skin Designations
- U.S. Minnesota Permissible Exposure Limits TWAs
- U.S. New Hampshire Regulated Toxic Air Pollutants Ambient Air Levels (AALs) 24-Hour
- U.S. New Hampshire Regulated Toxic Air Pollutants Ambient Air Levels (AALs) Annual
- U.S. New York Occupational Exposure Limits Skin Designations
- U.S. New York Occupational Exposure Limits TWAs
- U.S. North Dakota Air Pollutants Guideline Concentrations 1-Hour
- U.S. North Dakota Air Pollutants Guideline Concentrations 8-Hour
- U.S. Oregon Permissible Exposure Limits TWAs
- U.S. Tennessee Occupational Exposure Limits Skin Designations
- U.S. Tennessee Occupational Exposure Limits TWAs
- U.S. Texas Effects Screening Levels Long Term
- U.S. Texas Effects Screening Levels Short Term
- U.S. Vermont Permissible Exposure Limits Skin Designations
- U.S. Vermont Permissible Exposure Limits TWAs
- U.S. Washington Permissible Exposure Limits Skin Designations
- U.S. Washington Permissible Exposure Limits STELs
- U.S. Washington Permissible Exposure Limits TWAs

U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 25 Feet to Less Than 40 Feet

U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 40 Feet to Less Than 75 Feet

U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 75 Feet or Greater

U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights Less Than 25 Feet

Dibutyltin dilaurate (77-58-7)

U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - 24-Hour U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - Annual U.S. - California - Safer Consumer Products - Initial List of Candidate Chemicals and Chemical Groups U.S. - Texas - Effects Screening Levels - Long Term

U.S. - Texas - Effects Screening Levels - Short Term

SECTION 16: Other Information, Including Date of Preparation or Last Revision

Date of Preparation or Latest Revision	02/27/2023
Other Information	This document has been prepared in accordance with
	the SDS requirements of the OSHA Hazard
	Communication Standard 29 CER 1910 1200

GHS Full Text Phrases:

MED-1131

Safety Data Sheet According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Acute Tox. 4	Acute toxicity (inhalation:dust,mist) Category 4
(Inhalation:dust,mist)	
Aquatic Acute 1	Hazardous to the aquatic environment - Acute Hazard Category 1
Aquatic Acute 2	Hazardous to the aquatic environment - Acute Hazard Category 2
Aquatic Chronic 1	Hazardous to the aquatic environment - Chronic Hazard Category 1
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Eye Irrit. 2	Serious eye damage/eye irritation Category 2
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Muta. 2	Germ cell mutagenicity Category 2
Repr. 1B	Reproductive toxicity Category 1B
Skin Irrit. 2	Skin corrosion/irritation Category 2
Skin Sens. 1	Skin sensitization, Category 1
Skin Sens. 1B	Skin sensitization, category 1B
STOT RE 1	Specific target organ toxicity (repeated exposure) Category 1
STOT RE 2	Specific target organ toxicity (repeated exposure) Category 2
STOT SE 1	Specific target organ toxicity (single exposure) Category 1
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H319	Causes serious eye irritation
H332	Harmful if inhaled
H341	Suspected of causing genetic defects
H360	May damage fertility or the unborn child
H370	Causes damage to organs
H372	Causes damage to organs through prolonged or repeated exposure
H373	May cause damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life
H401	Toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects
FPA Health Hazard	2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.
FPA Fire Hazard	1 - Materials that must be preheated before ignition can occur.
FPA Reactivity Hazard	0 - Material that in themselves are normally stable, even under fire conditions.
MIS III Rating	
ealth	2 Moderate Hazard - Temporary or minor injury may occur * Chronic - Chronic (long-term) health effects may result from repeated overexposure
ammability hysical	1 Slight Hazard 0 Minimal Hazard

The information provided in this Safety Data Sheet (SDS) was prepared based on data believed to

be accurate as of the date of this SDS. TO THE GREATEST EXTENT PERMITTED BY LAW, NUSIL TECHNOLOGY LLC AND ITS AFFILIATED COMPANIES ("NUSIL") EXPRESSLY DISCLAIMS ANY AND ALL REPRESENTATIONS AND WARRANTIES REGARDING THE INFORMATION CONTAINED HEREIN INCLUDING, WITHOUT LIMITATION, AS TO ACCURACY, COMPLETENESS, FITNESS FOR PURPOSE OR USE, MERCHANTABILITY, NON-INFRINGEMENT, PERFORMANCE, SAFETY, SUITABILITY AND STABILITY. This SDS is intended as a guide to the appropriate use, handling, storage and disposal of the product to which it relates by properly trained personnel, and is not intended to be comprehensive. Users of NuSil's products are advised to perform their own tests and to exercise their own judgment to determine the safety, suitability and appropriate use, handling, storage and disposal of each product and product combination for their own purposes and uses. TO THE GREATEST EXTENT PERMITTED BY LAW, NUSIL DISCLAIMS LIABILITY FOR, AND BY USING NUSIL'S PRODUCTS PURCHASER AGREES THAT UNDER NO CIRCUMSTANCES SHALL NUSIL BE LIABLE FOR, SPECIAL, INDIRECT, INCIDENTAL, PUNITIVE OR CONSEQUENTIAL DAMAGES OF ANY TYPE OR KIND, INCLUDING WITHOUT LIMITATION, FOR LOSS OF PROFITS, REPUTATIONAL DAMAGE, PRODUCT RECALL OR BUSINESS INTERRUPTION.

NUSII US GHS SDS