

# FS-3730-11

## Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations  
Revision Date: 07/18/2022 Date of Issue: 03/18/2014



Version: 4.0

## SECTION 1: Identification

### 1.1. Product Identifier

Product Form Mixture  
Product Name FS-3730-11  
Synonyms Fluorosilicone Adhesive

### 1.2. Relevant Identified Uses of the Substance or Mixture and Uses Advised Against

Use of the Substance/Mixture For professional use only.

### 1.3. Details of the Supplier of the Safety Data Sheet

NuSil Technology LLC  
1050 Cindy Lane  
Carpinteria, California 93013  
USA  
(805) 684-8780  
[productstewardship@avantorsciencesgcc.com](mailto:productstewardship@avantorsciencesgcc.com)  
[www.nusil.com](http://www.nusil.com)

### 1.4. Emergency Telephone Number

Emergency Number 800-424-9300 CHEMTREC (in US); +1 703-527-3887 CHEMTREC (International and Maritime)

## SECTION 2: Hazards Identification

### 2.1. Classification of the Substance or Mixture

#### GHS-US Classification

Skin Corr. 1B H314  
Eye Dam. 1 H318  
STOT SE 3 H335

Full text of hazard classes and H-statements: see section 16

### 2.2. Label Elements

#### GHS-US Labeling

Hazard Pictograms (GHS-US)



GHS05



GHS07

Signal Word (GHS-US)

Danger

Hazard Statements (GHS-US)

H314 - Causes severe skin burns and eye damage  
H318 - Causes serious eye damage  
H335 - May cause respiratory irritation

# FS-3730-11

## Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### Precautionary Statements (GHS-US)

P260 - Do not breathe vapors, mist, or spray.  
P264 - Wash hands, forearms, and other exposed areas thoroughly after handling.  
P271 - Use only outdoors or in a well-ventilated area.  
P280 - Wear protective gloves, protective clothing, and eye protection.  
P301+P330+P331 - If swallowed: rinse mouth. Do NOT induce vomiting.  
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
P304+P340 - If inhaled: Remove person to fresh air and keep at rest in a position comfortable for breathing.  
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P310 - Immediately call a poison center or doctor.  
P321 - Specific treatment (see section 4 on this SDS).  
P363 - Wash contaminated clothing before reuse.  
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.  
P405 - Store locked up.  
P501 - Dispose of contents/container in accordance with local, regional, national, and international regulations.

### 2.3. Other Hazards

Other Hazards Not Contributing to the Classification

Exposure may aggravate pre-existing eye, skin, or respiratory conditions.

### 2.4. Unknown Acute Toxicity (GHS-US)

No additional information available

## SECTION 3: Composition/Information On Ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product Identifier	%	GHS-US Classification
Siloxanes and Silicones, methyl 3,3,3-trifluoropropyl, hydroxy-terminated	(CAS-No.) 68607-77-2	60 – 80	Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H335
Silanetriol, ethyl-, triacetate	(CAS-No.) 17689-77-9	< 10	Acute Tox. 4 (Oral), H302 Skin Corr. 1B, H314 Eye Dam. 1, H318
Titanium dioxide	(CAS No) 13463-67-7	< 3	Not classified
Glycidoxypropyltrimethoxysilane	(CAS No) 2530-83-8	< 1	Eye Dam. 1, H318
Chromium oxide (Cr2O3)	(CAS-No.) 1308-38-9	< 1	Not classified
Dibutyltin diacetate	(CAS-No.) 1067-33-0	< 0.1	Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1B, H317 Muta. 2, H341 Repr. 1B, H360 STOT SE 1, H370

			STOT RE 1, H372 Aquatic Chronic 1, H410
--	--	--	--

Full text of H-phrases: see section 1.6

The specific chemical identity and/or exact percentage of composition have been withheld as a trade secret [29 CFR 1910.1200].

**SECTION 4: First Aid Measures**

**4.1. Description of First-aid Measures**

First-aid Measures General	Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid Measures After Inhalation	Remove to fresh air and keep at rest in a position comfortable for breathing. Immediately call a poison center or doctor/physician.
First-aid Measures After Skin Contact	Immediately remove contaminated clothing. Immediately flush skin with plenty of water for at least 30 minutes. Get immediate medical advice/attention.
First-aid Measures After Eye Contact	Immediately rinse with water for at least 30 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical advice/attention.
First-aid Measures After Ingestion	Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

**4.2. Most Important Symptoms and Effects Both Acute and Delayed**

Symptoms/Injuries	May cause respiratory irritation. Causes severe skin burns and eye damage.
Symptoms/Injuries After Inhalation	Irritation of the respiratory tract and the other mucous membranes. May be corrosive to the respiratory tract.
Symptoms/Injuries After Skin Contact	Redness, pain, swelling, itching, burning, dryness, and dermatitis. Causes severe irritation which will progress to chemical burns.
Symptoms/Injuries After Eye Contact	Contact causes severe irritation with redness and swelling of the conjunctiva. Causes permanent damage to the cornea, iris, or conjunctiva.
Symptoms/Injuries After Ingestion	May cause burns or irritation of the linings of the mouth, throat, and gastrointestinal tract.
Chronic Symptoms	None expected under normal conditions of use.

**4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed**

If exposed or concerned, get medical advice and attention. If medical advice is needed, have product container or label at hand.

**SECTION 5: Fire-Fighting Measures**

**5.1. Extinguishing Media**

Suitable Extinguishing Media	: Water spray, fog, carbon dioxide (CO <sub>2</sub> ), alcohol-resistant foam, or dry chemical.
Unsuitable Extinguishing Media	: Application of water stream to hot product may cause frothing and increase fire intensity. Do not use a heavy water stream. Use of heavy stream of water may spread fire.

**5.2. Special Hazards Arising From the Substance or Mixture**

Fire Hazard	Not considered flammable but may burn at high temperatures.
Explosion Hazard	Product is not explosive.
Reactivity	May hydrolyze with water to form acetic acid. May react exothermically with water releasing heat. Adding an acid to a base or base to an acid may cause a violent reaction.

**5.3. Advice for Firefighters**

Precautionary Measures Fire	Under fire conditions, hazardous fumes will be present. Exercise caution when fighting any chemical fire.
Firefighting Instructions	Use water spray or fog for cooling exposed containers.
Protection During Firefighting	Do not enter fire area without proper protective equipment, including respiratory protection.
Hazardous Combustion Products	Carbon oxides (CO, CO <sub>2</sub> ). Silicon oxides. Formaldehyde.

**SECTION 6: Accidental Release Measures****6.1. Personal Precautions, Protective Equipment And Emergency Procedures**

General Measures	Do not breathe vapor, mist or spray. Do not get in eyes, on skin, or on clothing.
------------------	---

**6.1.1. For Non-Emergency Personnel**

Protective Equipment	Use appropriate personal protective equipment (PPE).
Emergency Procedures	Evacuate unnecessary personnel.

**6.1.2. For emergency responders**

Protective Equipment	Equip cleanup crew with proper protection.
Emergency Procedures	Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit. Ventilate area.

**6.2. Environmental Precautions**

Prevent entry to sewers and public waters.

**6.3. Methods and Materials for Containment and Cleaning Up**

For Containment	Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. As an immediate precautionary measure, isolate spill or leak area in all directions.
Methods for Cleaning Up	Clean up spills immediately and dispose of waste safely. Transfer spilled material to a suitable container for disposal. Contact competent authorities after a spill. Cautiously neutralize spilled liquid.

**6.4. Reference to Other Sections**

See Section 8 for exposure controls and personal protection and Section 13 for disposal considerations.

**SECTION 7: Handling And Storage****7.1. Precautions for Safe Handling**

Additional Hazards When Processed	When heated, material emits irritating fumes. May release corrosive vapors.
-----------------------------------	---

**Precautions for Safe Handling**

Do not breathe vapors, mist, and spray. Do not get in eyes, on skin, or on clothing. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Handle empty containers with care because they may still present a hazard.

**Hygiene Measures**

Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

**7.2. Conditions for Safe Storage, Including Any Incompatibilities**

**Technical Measures**

Comply with applicable regulations.

**Storage Conditions**

Keep container closed when not in use. Store in a dry, cool place. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials. Store locked up/in a secure area. Store in original container or corrosive resistant and/or lined container.

**Incompatible Materials**

Strong acids, strong bases, strong oxidizers.

**7.3. Specific End Use(s)**

For professional use only.

**SECTION 8: Exposure Controls/Personal Protection**

**8.1. Control Parameters**

For substances listed in section 3 that are not listed here, there are no established exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), or OSHA (PEL).

Titanium dioxide (13463-67-7)		
USA ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>
USA ACGIH	ACGIH chemical category	Not Classifiable as a Human Carcinogen
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	15 mg/m <sup>3</sup> (total dust)
Chromium oxide (Cr <sub>2</sub> O <sub>3</sub> ) (1308-38-9)		
USA ACGIH	ACGIH OEL TWA	0.05 mg/m <sup>3</sup> 0.5 (Cr II & Cr III Compounds) 0.05 (Cr VI Water Soluble)
USA OSHA	OSHA PEL (TWA) [1]	1 mg/m <sup>3</sup> (metal) 0.5 (Cr II & Cr III Compounds) 0.005 (Cr VI Compounds)
Tin organic compounds		
USA ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	0.1 mg/m <sup>3</sup>
USA ACGIH	ACGIH STEL (mg/m <sup>3</sup> )	0.2 mg/m <sup>3</sup>
USA ACGIH	ACGIH chemical category	Skin - potential significant contribution to overall exposure by the cutaneous route, Not Classifiable as a Human Carcinogen
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	0.1 mg/m <sup>3</sup>

**8.2. Exposure Controls**

Appropriate Engineering Controls

Ensure adequate ventilation, especially in confined areas. Ensure all national/local regulations are observed. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

Personal Protective Equipment

Gloves. Protective clothing. Protective goggles. Face shield. Insufficient ventilation: wear respiratory protection.



Materials For Protective Clothing

Chemically resistant materials and fabrics. Corrosion-proof clothing.

Hand Protection

Wear protective gloves.

Eye And Face Protection

Chemical safety goggles and face shield.

Skin And Body Protection

Wear suitable protective clothing.

Respiratory Protection

If exposure limits are exceeded or irritation is experienced, approved respiratory protection should be worn. In case of inadequate ventilation, oxygen deficient atmosphere, or where exposure levels are not known wear approved respiratory protection.

Other Information

When using, do not eat, drink or smoke.

**SECTION 9: Physical and Chemical Properties**

**9.1. Information on Basic Physical and Chemical Properties**

Physical State	Liquid
Appearance	Gray
Odor	Acetic acid
Odor Threshold	No data available
pH	No data available
Evaporation Rate	No data available
Melting Point	No data available
Freezing Point	No data available
Boiling Point	No data available
Flash Point	> 135 °C (275 °F)
Auto-ignition Temperature	No data available
Decomposition Temperature	No data available
Flammability (solid, gas)	Not applicable
Vapor Pressure	No data available
Relative Vapor Density at 20 °C	No data available
Relative Density	No data available
Specific Gravity	> 1 (Water = 1)
Solubility	No data available
Partition Coefficient n-Octanol/Water	No data available
Viscosity	No data available

**9.2. Other Information**

VOC Content < 1%

## SECTION 10: Stability and Reactivity

### 10.1. Reactivity

May hydrolyze with water to form acetic acid. May react exothermically with water releasing heat. Adding an acid to a base or base to an acid may cause a violent reaction.

### 10.2. Chemical Stability

Stable under recommended handling and storage conditions (see section 7).

### 10.3. Possibility of Hazardous Reactions

Hazardous polymerization will not occur.

### 10.4. Conditions to Avoid

Direct sunlight, extremely high or low temperatures, and incompatible materials.

### 10.5. Incompatible Materials

Strong acids, strong bases, strong oxidizers.

### 10.6. Hazardous Decomposition Products

Thermal decomposition may produce: Corrosive vapors. Silicon oxides. Carbon oxides (CO, CO<sub>2</sub>). Formaldehyde. Will decompose above 150 °C (> 300 °F) releasing formaldehyde vapors.

Formaldehyde is a potential carcinogen and can act as a potential skin and respiratory sensitizer. Formaldehyde can also cause respiratory and eye irritation.

## SECTION 11: Toxicological Information

### 11.1. Information on Toxicological Effects

Acute Toxicity (Oral) : Not classified  
 Acute Toxicity (Dermal) : Not classified  
 Acute Toxicity (Inhalation) : Not classified

Titanium dioxide (13463-67-7)	
LD50 oral rat	> 10000 mg/kg
Glycidoxypropyltrimethoxysilane (2530-83-8)	
LD50 oral rat	8025 mg/kg
LD50 dermal rabbit	4250 mg/kg
ATE (Oral)	8,025.00 mg/kg body weight
ATE (Dermal)	4,250.00 mg/kg body weight
Silanetriol, ethyl-, triacetate (17689-77-9)	
LD50 Oral Rat	1460 mg/kg
Chromium oxide (Cr <sub>2</sub> O <sub>3</sub> ) (1308-38-9)	
LD50 Oral Rat	> 5000 mg/kg
LC50 Inhalation Rat	> 5.41 mg/l/4h

Skin Corrosion/Irritation Causes severe skin burns.  
 Serious Eye Damage/Irritation Causes serious eye damage.  
 Respiratory or Skin Sensitization Not classified  
 Germ Cell Mutagenicity Not classified  
 Carcinogenicity Not classified

Titanium dioxide (13463-67-7)	
IARC group	2B
OSHA Hazard Communication Carcinogen List	In OSHA Hazard Communication Carcinogen list.
Chromium oxide (Cr <sub>2</sub> O <sub>3</sub> ) (1308-38-9)	
IARC Group	3

# FS-3730-11

## Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Reproductive Toxicity	: Not classified
Specific Target Organ Toxicity (Single Exposure)	: May cause respiratory irritation.
Specific Target Organ Toxicity (Repeated Exposure)	: Not classified
Aspiration Hazard	Not classified
Symptoms/Injuries After Inhalation	Irritation of the respiratory tract and the other mucous membranes. May be corrosive to the respiratory tract.
Symptoms/Injuries After Skin Contact	Redness, pain, swelling, itching, burning, dryness, and dermatitis. Causes severe irritation which will progress to chemical burns.
Symptoms/Injuries After Eye Contact	Contact causes severe irritation with redness and swelling of the conjunctiva. Causes permanent damage to the cornea, iris, or conjunctiva.
Symptoms/Injuries After Ingestion	May cause burns or irritation of the linings of the mouth, throat, and gastrointestinal tract.
Chronic Symptoms	None expected under normal conditions of use.

## SECTION 12: Ecological Information

### 12.1. Toxicity

Ecology - General Not classified.

Titanium dioxide (13463-67-7)	
LC50 fish 1	> 1000 mg/l (Exposure Time: 96h - Species: Pimephales promelas (static))
Glycidoxypropyltrimethoxysilane (2530-83-8)	
LC50 fish 1	55 mg/l (Exposure time: 96 h - Species: Cyprinus carpio)
EC50 Daphnia 1	710 mg/l (Exposure time: 48 h - Species: Daphnia magna)
ErC50 (algae)	350 mg/l Exposure time: 96 h - Species: Pseudokirchnerella subcapitata)
Chromium oxide (Cr2O3) (1308-38-9)	
LC50 Fish 1	> 10000 mg/l (Exposure time: 96 h - Species: Danio rerio [static])
NOEC Chronic Fish	1000 mg/l (Species: Brachydanio rerio - Duration: 30 d)
Dibutyltin diacetate (1067-33-0)	
EC50 Chronic	0.035 mg/l Exposure time: 72 hour (Species: Skeletonema costatum)
NOEC (Acute)	0.65 mg/l
NOEC Chronic Crustacea	0.32 mg/l (48-Hour EC50 Daphnia magna)

### 12.2. Persistence and Degradability

FS-3730-11	
Persistence and Degradability	Not established.

### 12.3. Bioaccumulative Potential

FS-3730-11	
Bioaccumulative Potential	Not established.

### 12.4. Mobility In Soil

No additional information available



# FS-3730-11

## Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 12.5. Other Adverse Effects

Other Information Avoid release to the environment.

## SECTION 13: Disposal Considerations

### 13.1. Waste Treatment Methods

Waste Disposal Recommendations Dispose of waste material in accordance with all local, regional, national, and international regulations. Dispose of contents/container in accordance with local, regional, national, and international regulations.

Additional Information Container may remain hazardous when empty. Continue to observe all precautions.

Ecology - Waste Materials Avoid release to the environment.

## SECTION 14: Transport Information

The shipping description(s) stated herein were prepared in accordance with certain assumptions at the time the SDS was authored, and can vary based on a number of variables that may or may not have been known at the time the SDS was issued.

### 14.1. In Accordance with DOT

Proper Shipping Name CORROSIVE LIQUID, ACIDIC, ORGANIC, N.O.S. (CONTAINS: Silanetriol, ethyl-, triacetate)

Hazard Class 8

Identification Number UN3265

Label Codes 8

Packing Group II

ERG Number 153



### 14.2. In Accordance with IMDG

Proper Shipping Name CORROSIVE LIQUID, ACIDIC, ORGANIC, N.O.S. (CONTAINS: Silanetriol, ethyl-, triacetate)

Hazard Class 8

Identification Number UN3265

Packing Group II

Label Codes 8

EmS-No. (Fire) F-A

EmS-No. (Spillage) S-B

MFAG Number 154



### 14.3. In Accordance with IATA

Proper Shipping Name CORROSIVE LIQUID, ACIDIC, ORGANIC, N.O.S. (CONTAINS: Silanetriol, ethyl-, triacetate)

Packing Group II

Identification Number UN3265

Hazard Class 8

Label Codes 8

ERG Code (IATA) 8L



# FS-3730-11

## Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 15: Regulatory Information

#### 15.1. US Federal Regulations

All components in this mixture are listed on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory, have been exempted, are not listed, not disclosed due to CBI requirements or disclosure rules according to the relevant regulation.

FS-3730-11	
SARA Section 311/312 Hazard Classes	Health hazard - Specific target organ toxicity (single or repeated exposure) Health hazard - Serious eye damage or eye irritation Health hazard - Skin corrosion or Irritation

#### 15.2. US State Regulations

Silanetriol, ethyl-, triacetate (17689-77-9)	
U.S. - Texas - Effects Screening Levels - Long Term U.S. - Texas - Effects Screening Levels - Short Term	
Siloxanes and Silicones, methyl 3,3,3-trifluoropropyl, hydroxy-terminated (68607-77-2)	
U.S. - Texas - Effects Screening Levels - Long Term U.S. - Texas - Effects Screening Levels - Short Term	
Titanium dioxide (13463-67-7)	
U.S. - Connecticut - Hazardous Air Pollutants - HLVs (30 min) U.S. - Connecticut - Hazardous Air Pollutants - HLVs (8 hr) U.S. - Idaho - Occupational Exposure Limits - TWAs U.S. - Illinois - Toxic Air Contaminant Carcinogens RTK - U.S. - Massachusetts - Right To Know List U.S. - Michigan - Occupational Exposure Limits - TWAs U.S. - Minnesota - Chemicals of High Concern U.S. - Minnesota - Hazardous Substance List U.S. - Minnesota - Permissible Exposure Limits - TWAs U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - 24-Hour U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - Annual RTK - U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - New York - Occupational Exposure Limits - TWAs U.S. - North Dakota - Air Pollutants - Guideline Concentrations - 8-Hour U.S. - Oregon - Permissible Exposure Limits - TWAs U.S. - California - Safer Consumer Products - Initial List of Candidate Chemicals and Chemical Groups RTK - U.S. - Pennsylvania - RTK (Right to Know) List U.S. - Tennessee - Occupational Exposure Limits - TWAs U.S. - Texas - Effects Screening Levels - Long Term U.S. - Texas - Effects Screening Levels - Short Term U.S. - Vermont - Permissible Exposure Limits - TWAs U.S. - Washington - Permissible Exposure Limits - STELs U.S. - Washington - Permissible Exposure Limits - TWAs	
Titanium dioxide (13463-67-7)	
U.S. - California - Proposition 65 - Carcinogens List	WARNING: This product contains chemicals known to the State of California to cause cancer.
Glycidoxypropyltrimethoxysilane (2530-83-8)	
U.S. - Texas - Effects Screening Levels - Long Term	

# FS-3730-11

## Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

U.S. - Texas - Effects Screening Levels - Short Term
Chromium oxide (Cr2O3) (1308-38-9)
RTK - U.S. - New Jersey - Right to Know Hazardous Substance List RTK - U.S. - Massachusetts - Right To Know List U.S. - Texas - Effects Screening Levels - Long Term U.S. - Texas - Effects Screening Levels - Short Term
Tin organic compounds
U.S. - Connecticut - Hazardous Air Pollutants - HLVs (30 min) U.S. - Connecticut - Hazardous Air Pollutants - HLVs (8 hr) U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Emission Levels (ELs) U.S. - Michigan - Occupational Exposure Limits - Skin Designations U.S. - Michigan - Occupational Exposure Limits - TWAs U.S. - Minnesota - Hazardous Substance List U.S. - Minnesota - Permissible Exposure Limits - Skin Designations U.S. - Minnesota - Permissible Exposure Limits - TWAs U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - 24-Hour U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - Annual U.S. - New York - Occupational Exposure Limits - Skin Designations U.S. - New York - Occupational Exposure Limits - TWAs U.S. - North Dakota - Air Pollutants - Guideline Concentrations - 1-Hour U.S. - North Dakota - Air Pollutants - Guideline Concentrations - 8-Hour U.S. - Oregon - Permissible Exposure Limits - TWAs U.S. - Tennessee - Occupational Exposure Limits - Skin Designations U.S. - Tennessee - Occupational Exposure Limits - TWAs U.S. - Texas - Effects Screening Levels - Long Term U.S. - Texas - Effects Screening Levels - Short Term U.S. - Vermont - Permissible Exposure Limits - Skin Designations U.S. - Vermont - Permissible Exposure Limits - TWAs U.S. - Washington - Permissible Exposure Limits - Skin Designations U.S. - Washington - Permissible Exposure Limits - STELs U.S. - Washington - Permissible Exposure Limits - TWAs U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 25 Feet to Less Than 40 Feet U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 40 Feet to Less Than 75 Feet U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 75 Feet or Greater U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights Less Than 25 Feet
Dibutyltin diacetate (1067-33-0)
RTK - U.S. - Massachusetts - Right To Know List U.S. - Texas - Effects Screening Levels - Long Term U.S. - Texas - Effects Screening Levels - Short Term

## SECTION 16: Other Information, Including Date of Preparation or Last Revision

Date of Preparation or Latest Revision      07/18/2022

# FS-3730-11

## Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### Other Information

This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.

The specific chemical identity and/or exact percentage of composition have been withheld as a trade secret [29 CFR 1910.1200].

### GHS Full Text Phrases:


Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Aquatic Acute 3	Hazardous to the aquatic environment - Acute Hazard Category 3
Aquatic Chronic 1	Hazardous to the aquatic environment - Chronic Hazard Category 1
Aquatic Chronic 3	Hazardous to the aquatic environment - Chronic Hazard Category 3
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Muta. 2	Germ cell mutagenicity Category 2
Repr. 1B	Reproductive toxicity Category 1B
Skin Corr. 1B	Skin corrosion/irritation Category 1B
Skin Corr. 1C	Skin corrosion/irritation Category 1C
Skin Irrit. 2	Skin corrosion/irritation Category 2
Skin Sens. 1B	Skin sensitization, category 1B
STOT RE 1	Specific target organ toxicity (repeated exposure) Category 1
STOT SE 1	Specific target organ toxicity (single exposure) Category 1
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
H302	Harmful if swallowed
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H319	Causes serious eye irritation
H335	May cause respiratory irritation
H341	Suspected of causing genetic defects
H360	May damage fertility or the unborn child
H370	Causes damage to organs
H372	Causes damage to organs through prolonged or repeated exposure
H402	Harmful to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects

# FS-3730-11

## Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

NFPA Health Hazard	3 - Materials that, under emergency conditions, can cause serious or permanent injury.
NFPA Fire Hazard	1 - Materials that must be preheated before ignition can occur.
NFPA Reactivity Hazard	0 - Material that in themselves are normally stable, even under fire conditions.
HMIS III Rating	
Health	3 Serious Hazard
Flammability	1 Slight Hazard
Physical	0 Minimal Hazard



The information provided in this Safety Data Sheet (SDS) was prepared based on data believed to be accurate as of the date of this SDS. TO THE GREATEST EXTENT PERMITTED BY LAW, NUSIL TECHNOLOGY LLC AND ITS AFFILIATED COMPANIES ("NUSIL") EXPRESSLY DISCLAIMS ANY AND ALL REPRESENTATIONS AND WARRANTIES REGARDING THE INFORMATION CONTAINED HEREIN INCLUDING, WITHOUT LIMITATION, AS TO ACCURACY, COMPLETENESS, FITNESS FOR PURPOSE OR USE, MERCHANTABILITY, NON-INFRINGEMENT, PERFORMANCE, SAFETY, SUITABILITY AND STABILITY. This SDS is intended as a guide to the appropriate use, handling, storage and disposal of the product to which it relates by properly trained personnel, and is not intended to be comprehensive. Users of NuSil's products are advised to perform their own tests and to exercise their own judgment to determine the safety, suitability and appropriate use, handling, storage and disposal of each product and product combination for their own purposes and uses. TO THE GREATEST EXTENT PERMITTED BY LAW, NUSIL DISCLAIMS LIABILITY FOR, AND BY USING NUSIL'S PRODUCTS PURCHASER AGREES THAT UNDER NO CIRCUMSTANCES SHALL NUSIL BE LIABLE FOR, SPECIAL, INDIRECT, INCIDENTAL, PUNITIVE OR CONSEQUENTIAL DAMAGES OF ANY TYPE OR KIND, INCLUDING WITHOUT LIMITATION, FOR LOSS OF PROFITS, REPUTATIONAL DAMAGE, PRODUCT RECALL OR BUSINESS INTERRUPTION.

NuSil US GHS SDS